




CLAMPS



TEST



FILTRATION



DIAGTRONICS



ACCESSORIES



VALVES



FLANGES



ACCUMULATORS

Home

Test 20 - THR M16 x 2

Test 15 - THR M16 x 1.5

Test 12 - THR S12.65 x 1.5

Test 10 - Plug in


Adaptors

Pressure Gauges/Kits

Test Hoses

Technical

Stauff Test



STAUFF TEST has established a reputation for a comprehensive range of test points and accessories for hydraulic and pneumatic systems for many years now.

STAUFF TEST stands for a varied spectrum of screw-in test points and test couplings for tube fittings, which are oriented to international standards and therefore guaranteed to comply with the requirements of applications all over the world.

The extensive range of accessories, including measuring hoses and pressure gauges (mechanical and digital/electronic) means that the initial test points fitted onto machines and service kits with measuring instruments can be obtained from a single source.

All products are subject to our in-house quality management in accordance with EN ISO 9001:2008. This ensures a consistently high standard of quality.

Our company has also been certified in the fields of environmental protection acc. to DIN EN ISO 14001:2004 and occupational safety acc. to OHSAS 18001:2007.

Our well-stocked warehouse and flexible production line ensure prompt reactions and short delivery times. Furthermore, special versions that have been tailored to customer-specific requirements are available to order.

The following approvals are also available for special versions of the SKK test points:

- approved for military use as gas filling valve for nitrogen accumulators by the German Bundeswehr "Wehrtechnische Dienststelle für Pionier- und Truppengerät".
- DVGW registration as a test point for gas pressure control systems, issued by the German Association of Gas and Water Industries (DVGW). Please contact STAUFF for further details.



CLAMPS



TEST



FILTRATION



DIAGTRONICS



ACCESSORIES



VALVES



FLANGES



ACCUMULATORS



Home

Test 20 - THR M16 x 2

Test 15 - THR M16 x 1.5

Test 12 - THR S12.65 x 1.5

Test 10 - Plug in

Adaptors

Pressure Gauges/Kits

Test Hoses

Technical

Test 20 - Connection Thread M16 x 2 - SMK20

[Introduction - Test Coupling with Ball Check](#)

[Test Coupling with Port Connection SMK20](#)

[Test Coupling complete with Straight Fitting SMK20 Type G](#)

[Test Coupling for 24° Cone Fittings SMK20 Type K](#)

[Test Coupling SMK-JIC Connection SMK20-JIC Type K](#)

[Test Coupling SMK-JIC Connection SMK20-JIC Type G](#)

[Swivel Run Tee with JIC Connection SGV-JIC Type F/M](#)

[Test Coupling with ORFS Connection SMK20 Type ORFS](#)

[Bulkhead SSK20](#)

[Adaptor SAD20](#)

[Gauge Adaptor SMA20](#)

[Direct Gauge Adaptor SMD20](#)

Test 20 - Connection Thread M16 x 2 - SKK20

[Introduction - Test Coupling with Piston Valve](#)

[Test Coupling with Port Connection SKK20](#)

[Test Coupling complete with Straight Fitting SKK20 Type G](#)

[Test Coupling for 24° Cone Fittings SKK20 Type K](#)





CLAMPS



TEST



FILTRATION



DIAGTRONICS



ACCESSORIES



VALVES



FLANGES



ACCUMULATORS



Home

Test 20 - THR M16 x 2

Test 15 - THR M16 x 1.5

Test 12 - THR S12.65 x 1.5

Test 10 - Plug in

Adaptors

Pressure Gauges/Kits

Test Hoses

Technical

Test 15 - Connection Thread M16 x 1.5 B16

[Introduction - Test Coupling with Ball Check](#)

[Test Coupling with Port Connection SMK15](#)

[Test Coupling complete with Straight Fitting SMK15 Type G](#)

[Test Coupling for 24° Cone Fittings SMK15 Type K](#)

[Bulkhead SSK15](#)

[Swivel Run Tee with JIC Connection SGV-JIC Type F/M](#)

[Adaptor SAD15](#)

[Gauge Adaptor SMA15](#)

[Direct Gauge Adaptor SMD15](#)






CLAMPS



TEST



FILTRATION



DIAGTRONICS



ACCESSORIES



VALVES



FLANGES



ACCUMULATORS



Home

Test 20 - THR M16 x 2

Test 15 - THR M16 x 1.5

Test 12 - THR S12.65 x 1.5

Test 10 - Plug in

Adaptors

Pressure Gauges/Kits

Test Hoses

Technical

Test 12 - Connection Thread S12,65 x 1.5 B22

[Introduction - Test Coupling with Piston Valve](#)

[Test Coupling with Port Connection SKK12](#)

[Test Coupling complete with Straight Fitting SKK12 Type G](#)

[Test Coupling for 24° Cone Fittings SKK12 Type K](#)

[Bulkhead SSKK12](#)

[Swivel Run Tee with JIC Connection SGV-JIC Type F/M](#)

[Adaptor SAD12](#)

[Gauge Adaptor SMA12](#)

[Direct Gauge Adaptor SMD12](#)






CLAMPS



TEST



FILTRATION



DIAGNOSTICS



ACCESSORIES



VALVES



FLANGES



ACCUMULATORS



Home

Test 20 - THR M16 x 2

Test 15 - THR M16 x 1.5

Test 12 - THR S12.65 x 1.5

Test 10 - Plug in

Adaptors

Pressure Gauges/Kits

Test Hoses

Technical

Test 10 - Plug in system

[Test Coupling with Ball Check](#)

[Test Coupling with Port Connection SMK10](#)

[Gauge Adaptor SMA10](#)

[Test Coupling complete with Straight Fitting SMK10 Type G](#)

[Test Coupling for 24° Cone Fittings SMK10 Type K](#)






CLAMPS



TEST



FILTRATION



DIAGTRONICS



ACCESSORIES



VALVES



FLANGES



ACCUMULATORS



Home

Test 20 - THR M16 x 2

Test 15 - THR M16 x 1.5

Test 12 - THR S12.65 x 1.5

Test 10 - Plug in

Adaptors

Pressure Gauges/Kits

Test Hoses

Technical

Test Hoses / Hose Ends

[Technical Data for Test Hose SMS / SGS](#)


[Order Codes - Test Hose SMS / SGS and Hose End HE](#)

[Hose End HE](#)

[Hose Connector SSV](#)

[Sampling Hose Adaptor SHA](#)





STAUFF TEST has established a reputation for a comprehensive range of test points and accessories for hydraulic and pneumatic systems for many years now.

STAUFF TEST stands for a varied spectrum of screw-in test points and test couplings for tube fittings, which are oriented to international standards and therefore guaranteed to comply with the requirements of applications all over the world.

The extensive range of accessories, including measuring hoses and pressure gauges (mechanical and digital/electronic) means that the initial test points fitted onto machines and service kits with measuring instruments can be obtained from a single source.

All products are subject to our in-house quality management in accordance with EN ISO 9001:2008. This ensures a consistently high standard of quality.

Our company has also been certified in the fields of environmental protection acc. to DIN EN ISO 14001:2004 and occupational safety acc. to OHSAS 18001:2007.

Our well-stocked warehouse and flexible production line ensure prompt reactions and short delivery times. Furthermore, special versions that have been tailored to customer-specific requirements are available to order.

The following approvals are also available for special versions of the SKK test points:

- approved for military use as gas filling valve for nitrogen accumulators by the German Bundeswehr "Wehrtechnische Dienststelle für Pionier- und Truppengerät".
- DVGW registration as a test point for gas pressure control systems, issued by the German Association of Gas and Water Industries (DVGW).

Please contact STAUFF for further details.

www.stauff.com

B STAUFF Test

Index	B2
Test 20 - Connection Thread M16 x 2	B4
Test 15 - Connection Thread M16 x 1,5	B16
Test 12 - Connection Thread S12,65 x 1,5	B22
Test 10 - Plug in system	B28
Adaptors	B32
Pressure Gauges and Accessories	B34
Test Hoses / Hose Ends	B36
Technical Appendix	B46

Test 20 - Connection Thread M16 x 2 - SMK20

	Introduction - Test Coupling with Ball Check		B4
	Test Coupling with Port Connection	SMK20	B5
	Test Coupling complete with Straight Fitting	SMK20 Type G	B6
	Test Coupling for 24° Cone Fittings	SMK20 Type K	B7
	Test Coupling SMK-JIC Connection	SMK20-JIC Type K	B8
	Test Coupling SMK-JIC Connection	SMK20-JIC Type G	B8
	Swivel Run Tee with JIC Connection	SGV-JIC Type F/M	B9
	Test Coupling with ORFS Connection	SMK20 Type ORFS	B9
	Bulkhead	SSK20	B10
	Adaptor	SAD20	B11
	Gauge Adaptor Direct Gauge Adaptor	SMA20 SMD20	B11

Test 20 - Connection Thread M16 x 2 - SKK20

	Introduction - Test Coupling with Piston Valve		B12
	Test Coupling with Port Connection	SKK20	B13
	Test Coupling complete with Straight Fitting	SKK20 Type G	B14
	Test Coupling for 24° Cone Fittings	SKK20 Type K	B15

Test 15 - Connection Thread M16 x 1,5 - SMK15

	Introduction - Test Coupling with Ball Check		B16
	Test Coupling with Port Connection	SMK15	B17
	Test Coupling complete with Straight Fitting	SMK15 Type G	B18
	Test Coupling for 24° Cone Fittings	SMK15 Type K	B19
	Bulkhead	SSK15	B20
	Swivel Run Tee with JIC Connection	SGV-JIC Type F/M	B20
	Adaptor	SAD15	B21
	Gauge Adaptor Direct Gauge Adaptor	SMA15 SMD15	B21

Test 12 - Connection Thread S12,65 x 1,5 - SKK12

	Introduction - Test Coupling with Piston Valve		B22
	Test Coupling with Port Connection	SKK12	B23
	Test Coupling complete with Straight Fitting	SKK12 Type G	B24
	Test Coupling for 24° Cone Fittings	SKK12 Type K	B25
	Bulkhead	SSKK12	B26
	Swivel Run Tee with JIC Connection	SGV-JIC Type F/M	B26
	Adaptor	SAD12	B27
	Gauge Adaptor Direct Gauge Adaptor	SMA12 SMD12	B27

Test 10 - Plug In System - SMK10

Test Hoses

Introduction - Test Coupling with Ball Check		B28	Technical Data for Test Hose		SMS / SGS	B36	
	Test Coupling with Port Connection	SMK10	B29		Order Codes Test Hose / Hose End	SMS / SGS and HE	B37
	Gauge Adaptor	SMA10	B29		Hose End	HE	B38
	Test Coupling complete with Straight Fitting	SMK10 Type G	B30		Hose Connector	SSV	B44
	Test Coupling for 24° Cone Fittings	SMK10 Type K	B31		Sampling Hose Adaptor	SHA	B44

Adaptors


Technical Appendix

	Thread Adaptor	SRS20	B32	Port Connections and Sealing Details		B46
	Thread Adaptor	SRS15	B33			
	Welding Adaptor	SAS	B33			

Pressure Gauges and Accessories

	Pressure Gauge	SPG	B34
	Adjustable Gauge Fitting	EMV	B34
	Pressure Test Kit	SMB	B35

Test Coupling with Ball Check



Fast Coupling for

- Monitoring and control of pressure
- Venting
- Sampling in high- and low-pressure systems

Advantages

- Test system at working pressure
- Leak proof connection before **ball check** is open
- Simple connection to measurement, control and switching devices
- Self locking metal protective cap

Working Pressure

- Max. working pressure 630 bar / 9137 PSI
For SMK Type G and K the recommended working pressure of fitting manufacturer should be noted.
- Connection under pressure up to 400 bar / 5801 PSI max.

Materials

- Metal Parts:**
Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
Optional:
Stainless Steel **V2A** (1.4305 / AISI 303) on request
Stainless Steel **V4A** (1.4571 / AISI 316Ti) on request

For ordering "V2A" or "V4A" please replace "C6F" with "V2A" or "V4A".

- Ball:** Stainless Steel

Sealings:

P = NBR (Buna-N®)

(Temperature range -20 °C ... +100 °C / -4 °F ... +212 °F)

Note: Internal sealings made of FPM, even for standard NBR-type.

V = FPM (Viton®)*

(Temperature range -20 °C ... +200 °C / -4 °F ... +392 °F)

*** Standard option for North America is FPM (Viton®)**

E = EPDM Ethylene Propylene Diene Monomer Rubber

(for Brake fluid,

Temperature range -40 °C ... +150 °C / -40 °F ... +302 °F)

For ordering NBR or EPDM sealings please replace "V" with "P" or "E".

Vibration safety O-ring made of NBR (Buna-N®) (standard).

Media

- Suitable for hydraulic oils and other Mineral oil based fluids
(Check compatibility of sealing material)
- For use with other liquid media please consult STAUFF



Protection Cap

- The complete STAUFF-Test-20-type-SMK range is also available with a hexagonal protection cap made of steel or plastic protection cap.

For ordering the hexagonal protection cap version please add "-SK" to the order code.
(e.g. SMK20-M10x1-VA-SK-C6F)

For ordering the plastic protection cap version please add "-KK" to the order code.
(e.g. SMK20-M10x1-VA-KK-C6F)

SMK20 Test Coupling with Port Connection	SMK20 Type G Test Coupling complete with Straight Fitting	SMK20 Type K Test Coupling for 24° Cone Fittings	SMK20-JIC Test Coupling SMK-JIC Connection (to SAE J514)	SSK20 Bulkhead



Test Coupling with Port Connection SMK20



Thread G	Sealing	Working Pressure (bar/psi)	Dimensions (mm/in)			Order Codes	
			h1	h2	Hex	NBR	FPM* (Standard Option-North America)
M8 x 1	Type A	250	38	8.5	17	SMK20-M8x1-PA-C6F	SMK20-M8x1-VA-C6F
		3625	1.50	.33	.67		
		630	38	9.8	17		
M10 x 1	Type A	9137	1.50	.39	.67	SMK20-M10x1-PA-C6F	SMK20-M10x1-VA-C6F
		400	37	8	17		
		5801	1.46	.31	.67		
M10 x 1	Type B	630	37	12	17	SMK20-M10x1-PB-C6F	SMK20-M10x1-VB-C6F
		9137	1.46	.47	.67		
		630	37	12	17		
M12 x 1,5	Type B	9137	1.46	.47	.67	SMK20-M12x1,5-PB-C6F	SMK20-M12x1,5-VB-C6F
		630	37	12	19		
		9137	1.46	.47	.75		
M14 x 1,5	Type B	630	37	12	19	SMK20-M14x1,5-PB-C6F	SMK20-M14x1,5-VB-C6F
		9137	1.46	.47	.75		
		630	37	12	22		
M16 x 1,5	Type B	9137	1.46	.47	.87	SMK20-M16x1,5-PB-C6F	SMK20-M16x1,5-VB-C6F
		400	39	8	17		
		5801	1.54	.31	.67		
G1/8	Type B	630	37	12	19	SMK20-G1/8-PB-C6F	SMK20-G1/8-VB-C6F
		9137	1.46	.47	.75		
		630	37	12	19		
G1/4	Type B	9137	1.46	.47	.75	SMK20-G1/4-PB-C6F	SMK20-G1/4-VB-C6F
		630	37	12	22		
		9137	1.46	.47	.87		
G3/8	Type B	630	37	12	22	SMK20-G3/8-PB-C6F	SMK20-G3/8-VB-C6F
		9137	1.46	.47	.87		
		400	39	8	17		
M10 x 1	Type C	5801	1.54	.31	.67	SMK20-M10x1-PC-C6F	SMK20-M10x1-VC-C6F
		630	37	12	17		
		9137	1.46	.47	.67		
M12 x 1,5	Type C	630	37	12	19	SMK20-M12x1,5-PC-C6F	SMK20-M12x1,5-VC-C6F
		9137	1.46	.47	.75		
		630	37	12	19		
M14 x 1,5	Type C	9137	1.46	.47	.75	SMK20-M14x1,5-PC-C6F	SMK20-M14x1,5-VC-C6F
		630	37	12	22		
		9137	1.46	.47	.87		
M16 x 1,5	Type C	630	37	12	22	SMK20-M16x1,5-PC-C6F	SMK20-M16x1,5-VC-C6F
		9137	1.46	.47	.87		
		400	39	8	17		
G1/8	Type C	5801	1.54	.31	.67	SMK20-G1/8-PC-C6F	SMK20-G1/8-VC-C6F
		630	37	12	19		
		9137	1.46	.47	.75		
G1/4	Type C	9137	1.46	.47	.75	SMK20-G1/4-PC-C6F	SMK20-G1/4-VC-C6F
		630	37	12	22		
		9137	1.46	.47	.87		
G3/8	Type C	630	37	12	22	SMK20-G3/8-PC-C6F	SMK20-G3/8-VC-C6F
		9137	1.46	.47	.87		
		630	39	14	27		
G1/2	Type C	9137	1.54	.55	1.06	SMK20-G1/2-PC-C6F	SMK20-G1/2-VC-C6F
		400	37	8	17		
		5801	1.46	.31	.67		
R1/8 K	Type D	630	35	12	17	SMK20-R1/8K-PD-C6F	SMK20-R1/8K-VD-C6F
		9137	1.38	.47	.67		
		400	36	10	17		
R1/4 K	Type D	5801	1.42	.39	.67	SMK20-R1/4K-PD-C6F	SMK20-R1/4K-VD-C6F
		630	35	15	17		
		9137	1.38	.59	.67		
1/8 NPT	Type D	630	35	15	17	SMK20-1/8NPT-PD-C6F	SMK20-1/8NPT-VD-C6F
		9137	1.38	.59	.67		
		400	38	7.5	17		
1/4 NPT	Type D	5.801	1.50	.30	.67	SMK20-1/4NPT-PD-C6F	SMK20-1/4NPT-VD-C6F
		630	38	9.1	17		
		9137	1.50	.36	.67		
5/16-24 UNF	Type E	630	38	9.2	17	SMK20-5/16UNF-PE-C6F	SMK20-5/16UNF-VE-C6F
		9137	1.50	.36	.67		
		630	37	10	19		
7/16-20 UNF	Type E	9137	1.46	.39	.75	SMK20-7/16UNF-PE-C6F	SMK20-7/16UNF-VE-C6F
		630	37	11.1	19		
		9137	1.46	.44	.75		
1/2-20 UNF	Type E	630	38	9.5	17	SMK20-1/2UNF-PE-C6F	SMK20-1/2UNF-VE-C6F
		9137	1.50	.37	.67		
		630	37	11	17		
9/16-18 UNF	Type E	9137	1.46	.43	.67	SMK20-9/16UNF-PE-C6F	SMK20-9/16UNF-VE-C6F
		630	38	11	19		
		9137	1.50	.43	.75		
3/4-16 UNF	Type E	630	37	11	17	SMK20-3/4UNF-PE-C6F	SMK20-3/4UNF-VE-C6F
		9137	1.46	.43	.67		
		630	38	11	19		
M10 x 1	Type E	9137	1.50	.43	.75	SMK20-M10x1-PE-C6F	SMK20-M10x1-VE-C6F
		630	37	11	17		
		9137	1.46	.43	.67		
M12 x 1,5	Type E	630	38	11	19	SMK20-M12x1,5-PE-C6F	SMK20-M12x1,5-VE-C6F
		9137	1.50	.43	.75		
		630	37	11	17		
M14 x 1,5	Type E	9137	1.50	.43	.75	SMK20-M14x1,5-PE-C6F	SMK20-M14x1,5-VE-C6F
		630	38	11	19		
		9137	1.50	.43	.75		

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Sealing Details



O-ring Type A



Metal Joint Type B



Elastomeric Sealing Type C



Taper Type D
(suitable sealant required)



O-ring Type E


Protection Cap

Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SMK20-M10x1-VA-SK-C6F)
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SMK20-M10x1-VA-KK-C6F)

For further information on materials, sealings or protection caps, please see page B4.

Other port connections and sealings on request.
Please consult STAUFF for further information.

Test Coupling complete with Straight Fitting SMK20 Type G



- Compression ring fittings acc. to ISO 8434-1 / DIN 2353

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".



* Standard option for North America is FPM (Viton®).

Protection Cap

Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SMK20-08L-VG-SK-C6F)
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SMK20-08L-VG-KK-C6F)

For further information on materials, sealings or protection caps, please see page B4.

Series	PN (^{bar} /psi)	Pipe Ø d	Dimensions (mm/in)						Order Codes	
			~I1	I2	h	Hex A	Hex B		NBR	FPM* (Standard Option-North America)
L	315 4568	6	51 2.01	21 .83	49 1.93	24 .94	14 .55		SMK20-06L-PG-C6F	SMK20-06L-VG-C6F
		8	51 2.01	21 .83	49 1.93	24 .94	17 .67		SMK20-08L-PG-C6F	SMK20-08L-VG-C6F
		10	53 2.09	23 .91	49 1.93	24 .94	19 .75		SMK20-10L-PG-C6F	SMK20-10L-VG-C6F
		12	53 2.09	23 .91	50,5 1.99	27 1.06	22 .87		SMK20-12L-PG-C6F	SMK20-12L-VG-C6F
		15	55 2.17	25 .98	52 2.05	30 1.18	27 1.06		SMK20-15L-PG-C6F	SMK20-15L-VG-C6F
		18	57 2.24	24 .94	53 2.09	32 1.26	32 1.26		SMK20-18L-PG-C6F	SMK20-18L-VG-C6F
	160 2320	22	61 2.40	28 1.10	55 2.17	36 1.42	36 1.42		SMK20-22L-PG-C6F	SMK20-22L-VG-C6F
		28	61 2.40	28 1.10	57,5 2.26	41 1.61	41 1.61		SMK20-28L-PG-C6F	SMK20-28L-VG-C6F
		35	69 2.72	26 1.02	60 2.36	46 1.81	50 1.97		SMK20-35L-PG-C6F	SMK20-35L-VG-C6F
		42	71 2.80	25 .98	64,5 2.54	55 2.17	60 2.36		SMK20-42L-PG-C6F	SMK20-42L-VG-C6F
	S	6	55 2.17	25 .98	49 1.93	24 .94	17 .67		SMK20-06S-PG-C6F	SMK20-06S-VG-C6F
		8	55 2.17	25 .98	49 1.93	24 .94	19 .75		SMK20-08S-PG-C6F	SMK20-08S-VG-C6F
		10	57 2.24	24 .94	49 1.93	24 .94	22 .87		SMK20-10S-PG-C6F	SMK20-10S-VG-C6F
		12	57 2.24	24 .94	49 1.93	24 .94	24 .94		SMK20-12S-PG-C6F	SMK20-12S-VG-C6F
		14	63 2.50	27 1.06	50,5 1.99	27 1.06	27 1.06		SMK20-14S-PG-C6F	SMK20-14S-VG-C6F
		16	63 2.50	26 1.02	52 2.05	30 1.18	30 1.18		SMK20-16S-PG-C6F	SMK20-16S-VG-C6F
		20	69 2.72	26 1.02	55 2.17	36 1.42	36 1.42		SMK20-20S-PG-C6F	SMK20-20S-VG-C6F
		25	75 2.95	27 1.06	57,5 2.26	41 1.61	46 1.81		SMK20-25S-PG-C6F	SMK20-25S-VG-C6F
		30	81 3.19	28 1.10	60 2.36	46 1.81	50 1.97		SMK20-30S-PG-C6F	SMK20-30S-VG-C6F
		315 4568	91 3.58	29 1.14	64,5 2.54	55 2.17	60 2.36		SMK20-38S-PG-C6F	SMK20-38S-VG-C6F



Test Coupling for 24° Cone Fittings SMK20 Type K



Version A

Version B

Series	PN (bar/psi)	Pipe Ø d	Dimensions (mm/in)			Thread	Version	Order Codes	
			I3	Hex A	G			NBR	FPM* (Standard Option-North America)
L	315 4568	6	15,5 .61	14 .55		M12 x 1,5	A	SMK20-06L-PK-C6F	SMK20-06L-VK-C6F
		8	15,5 .61	17 .67		M14 x 1,5	A	SMK20-08L-PK-C6F	SMK20-08L-VK-C6F
		10	16,5 .65	19 .75		M16 x 1,5	A	SMK20-10L-PK-C6F	SMK20-10L-VK-C6F
		12	17,5 .69	22 .87		M18 x 1,5	A	SMK20-12L-PK-C6F	SMK20-12L-VK-C6F
		15	21 .83	27 1.06		M22 x 1,5	B	SMK20-15L-PK-GS-C6F	SMK20-15L-VK-GS-C6F
		18	19,5 .77	32 1.26		M26 x 1,5	B	SMK20-18L-PK-GS-C6F	SMK20-18L-VK-GS-C6F
	160 2320	22	20,5 .81	36 1.42		M30 x 2	B	SMK20-22L-PK-GS-C6F	SMK20-22L-VK-GS-C6F
		28	25 .98	41 1.61		M36 x 2	B	SMK20-28L-PK-GS-C6F	SMK20-28L-VK-GS-C6F
		35	30 1.18	50 1.97		M45 x 2	B	SMK20-35L-PK-GS-C6F	SMK20-35L-VK-GS-C6F
		42	31 1.22	60 2.36		M52 x 2	B	SMK20-42L-PK-GS-C6F	SMK20-42L-VK-GS-C6F
S	630 9137	6	14,5 .57	17 .67		M14 x 1,5	A	SMK20-06S-PK-C6F	SMK20-06S-VK-C6F
		8	16,5 .65	19 .75		M16 x 1,5	A	SMK20-08S-PK-C6F	SMK20-08S-VK-C6F
		10	16,5 .65	22 .87		M18 x 1,5	A	SMK20-10S-PK-C6F	SMK20-10S-VK-C6F
		12	17,5 .69	24 .94		M20 x 1,5	A	SMK20-12S-PK-C6F	SMK20-12S-VK-C6F
		14	19,5 .77	27 1.06		M22 x 1,5	B	SMK20-14S-PK-GS-C6F	SMK20-14S-VK-GS-C6F
	400 5801	16	18 .71	30 1.18		M24 x 1,5	B	SMK20-16S-PK-GS-C6F	SMK20-16S-VK-GS-C6F
		20	24 .94	36 1.42		M30 x 2	B	SMK20-20S-PK-GS-C6F	SMK20-20S-VK-GS-C6F
		25	26 1.02	46 1.81		M36 x 2	B	SMK20-25S-PK-GS-C6F	SMK20-25S-VK-GS-C6F
		30	30 1.18	50 1.97		M42 x 2	B	SMK20-30S-PK-GS-C6F	SMK20-30S-VK-GS-C6F
	315 4568	38	34 1.34	60 2.36		M52 x 2	B	SMK20-38S-PK-GS-C6F	SMK20-38S-VK-GS-C6F

- For DKO connection
- According to ISO 8434-1 / DIN 2353
- Version A: one-piece design
- Version B: screwed design

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".


* Standard option for North America is FPM (Viton®).

Protection Cap


Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SMK20-08L-VK-SK-C6F)
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SMK20-08L-VK-KK-C6F)

For further information on materials, sealings or protection caps, please see page B4.

Test Coupling SMK-JIC Connection (to SAE-J514) SMK20-JIC Type K



Version A



Version B

- 37° JIC fittings acc. to SAE J514
- Version A: one-piece design
- Version B: screwed design

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is **FPM (Viton®)**.


Protection Cap

Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SMK20-JIC5/16-VK-SK-C6F)
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SMK20-JIC5/16-VK-KK-C6F)

Pipe Ø d inch	JIC Size	Dimensions (mm/in)	Thread G	Version	Order Codes NBR	FPM* (Standard Option-North America)
		h Hex A Hex B				
1/4	-4	53 17 17 2.09 .67 .67	7/16-20 UNF	A	SMK20-JIC1/4-PK-C6F	SMK20-JIC1/4-VK-C6F
5/16	-5	53,5 17 17 2.11 .67 .67	1/2-20 UNF	A	SMK20-JIC5/16-PK-C6F	SMK20-JIC5/16-VK-C6F
3/8	-6	55,5 19 17 2.19 .75 .67	9/16-18 UNF	A	SMK20-JIC3/8-PK-C6F	SMK20-JIC3/8-VK-C6F
1/2	-8	56,5 22 19 2.22 .87 .75	3/4-16 UNF	A	SMK20-JIC1/2-PK-C6F	SMK20-JIC1/2-VK-C6F
5/8	-10	60 27 22 2.36 1.06 .87	7/8-14 UNF	A	SMK20-JIC5/8-PK-C6F	SMK20-JIC5/8-VK-C6F
3/4	-12	70,5 32 - 2.78 1.26 -	1-1/16-12 UN	B	SMK20-JIC3/4-PK-GS-C6F	SMK20-JIC3/4-VK-GS-C6F
1	-16	69 38 - 2.72 1.50 -	1-5/16-12 UN	B	SMK20-JIC1-PK-GS-C6F	SMK20-JIC1-VK-GS-C6F
1-1/4	-20	73,5 50 - 2.89 1.97 -	1-5/8-12 UN	B	SMK20-JIC1-1/4-PK-GS-C6F	SMK20-JIC1-1/4-VK-GS-C6F
1-1/2	-24	76 60 - 2.99 2.36 -	1-7/8-12 UN	B	SMK20-JIC1-1/2-PK-GS-C6F	SMK20-JIC1-1/2-VK-GS-C6F

For further information on materials, sealings or protection caps, please see page B4.

Test Coupling SMK-JIC Connection (to SAE-J514) SMK20-JIC Type G



- 37° JIC fittings acc. to SAE J514

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".


* Standard option for North America is **FPM (Viton®)**.

Protection Cap

Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SMK20-JIC5/16-VG-SK-C6F)
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SMK20-JIC5/16-VG-KK-C6F)

Pipe Ø d inch	JIC Size	Dimensions (mm/in)	Thread G	Order Codes NBR	FPM* (Standard Option-North America)
		l1 l2 h Hex A			
1/4	-4	43 14 61 24 1.69 .55 2.40 .94	7/16-20 UNF	SMK20-JIC1/4-PG-C6F	SMK20-JIC1/4-VG-C6F
5/16	-5	43 14 61 24 1.69 .55 2.40 .94	1/2-20 UNF	SMK20-JIC5/16-PG-C6F	SMK20-JIC5/16-VG-C6F
3/8	-6	43 14 61 24 1.69 .55 2.40 .94	9/16-18 UNF	SMK20-JIC3/8-PG-C6F	SMK20-JIC3/8-VG-C6F
1/2	-8	48,5 16,5 67 30 1.91 .65 2.64 1.18	3/4-16 UNF	SMK20-JIC1/2-PG-C6F	SMK20-JIC1/2-VG-C6F
5/8	-10	53,5 19,5 67 30 2.11 .77 2.64 1.18	7/8-14 UNF	SMK20-JIC5/8-PG-C6F	SMK20-JIC5/8-VG-C6F
3/4	-12	59 22 73 36 2.32 .87 2.87 1.42	1-1/16-12 UN	SMK20-JIC3/4-PG-C6F	SMK20-JIC3/4-VG-C6F
1	-16	61 23 78 41 2.40 .91 3.07 1.61	1-5/16-12 UN	SMK20-JIC1-PG-C6F	SMK20-JIC1-VG-C6F
1-1/4	-20	65,5 24,5 83 46 2.58 .96 3.26 1.81	1-5/8-12 UN	SMK20-JIC1-1/4-PG-C6F	SMK20-JIC1-1/4-VG-C6F
1-1/2	-24	72 27,5 92 55 2.83 1.08 3.62 2.17	1-7/8-12 UN	SMK20-JIC1-1/2-PG-C6F	SMK20-JIC1-1/2-VG-C6F

For further information on materials, sealings or protection caps, please see page B4.



Swivel Run Tee with JIC Connection SGV-JIC Type F/M




Thread	Dimensions (^{mm} / _{in})								Order Codes
inch	Ø d1	Ø d2	l1	l2	l3	l4	Hex A	Hex B	
7/16–20 UNF	7,49	4,9	9	14	37	8	27	17	SGV-7/16UNF-04-JIC1/4-F/M-C6F
	.29	.19	.35	.55	1.46	.31	1.06	.67	
9/16–18 UNF	11,05	8,1	10,5	14	37,5	8,5	27	19	SGV-7/16UNF-06-JIC3/8-F/M-C6F
	.44	.32	.41	.55	1.48	.33	1.06	.75	
3/4–16 UNF	15,9	10,8	10,5	16,7	43,7	12	30	22	SGV-7/16UNF-08-JIC1/2-F/M-C6F
	.63	.43	.41	.66	1.72	.47	1.18	.87	
1-1/16–12 UNF	21,6	16,9	15,4	21,9	50,4	13,5	36	32	SGV-7/16UNF-12-JIC3/4-F/M-C6F
	.85	.66	.61	.86	1.98	.53	1.42	1.26	
1-5/16–12 UNF	27,9	23,2	17,3	23,1	53,1	15	41	41	SGV-7/16UNF-16-JIC1-F/M-C6F
	1.10	.91	.68	.91	2.09	.59	1.61	1.61	

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

For further information please consult STAUFF.



Test Coupling with ORFS Connection SMK20 Type ORFS



Thread	Dimensions (mm/in)				Order Codes	
	h	l	Hex A	Hex B	NBR	FPM* (Standard Option-North America)
9/16-18 UNF	54	19	17	17	SMK20-04-ORFS-P-C6F	SMK20-04-ORFS-V-C6F
	2.1	.75	.67	.67		
11/16-16 UNF	54	19	19	21	SMK20-06-ORFS-P-C6F	SMK20-06-ORFS-V-C6F
	2.1	.75	.75	.80		
13/16-16 UNF	54	19	22	24	SMK20-08-ORFS-P-C6F	SMK20-08-ORFS-V-C6F
	2.1	.75	.87	.87		

For further information on materials, sealings or protection caps, please see page B4.

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings





For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Protection Cap

Standard material: Steel
For ordering the hexagonal protection cap version please add
"-SK" to the order code. (e.g. SMK20-04-ORFS-V-SK-C6F)
For ordering the plastic protection cap version please add
"-KK" to the order code. (e.g. SMK20-04-ORFS-V-KK-C6F)

Bulkhead SSK20



Version A

Version B

Version C

Version D

- Also available for gaseous media Type SSKK

Threads

*1 Compression ring assembly 08L/ 08S/ 12L according to ISO 8434-1 / DIN 2353

*2 JIC cone fitting according to SAE J514

*3 O-ring face sealing according to SAE J1453

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**

For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".

For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".

For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Protection Cap

Standard material: Steel

For ordering the hexagonal protection cap version please add

"-SK" to the order code. (e.g. SSK20-V-SK-C6F)

For ordering the plastic protection cap version please add


"-KK" to the order code. (e.g. SSK20-V-KK-C6F)

For further information on materials, sealings or protection caps, please see page B4.


Note: Standard option version B without compression ring and nut.

Thread	Dimensions (mm/in)		Version	Order Codes	
	G	Hex		NBR	FPM* (Standard Option-North America)
M16	72	19	A	SSK20-P-C6F	SSK20-V-C6F
	2.83	.75			
M14 x 1,5*1	72	19	B	SSK20/08L-P-C6F	SSK20/08L-V-C6F
	2.83	.75			
M16 x 1,5*1	72	22	B	SSK20/08S-P-C6F	SSK20/08S-V-C6F
	2.83	.87			
M18 x 1,5*1	72	22	B	SSK20/12L-P-C6F	SSK20/12L-V-C6F
	2.83	.87			
7/16-20 UNF*2	66	17	C	SSK20/J7/16UNF-MV-P-C6F	SSK20/J7/16UNF-MV-V-C6F
	2.60	.67			
9/16-18 UNF*3	67	22	D	SSK20-04-ORFS-P-C6F	SSK20-04-ORFS-V-C6F
	2.64	.87			
11/16-16 UNF*3	72	27	D	SSK20-06-ORFS-P-C6F	SSK20-06-ORFS-V-C6F
	2.83	1.06			
13/16-16 UNF*3	75	30	D	SSK20-08-ORFS-P-C6F	SSK20-08-ORFS-V-C6F
	2.95	1.18			

**Adaptor
SAD20**



Version A



Version B



Thread	Dimensions (mm/in)	Version	Order Codes NBR	FPM* (Standard Option-North America)
G	h			
M16 x 1,5	39 1.54	A	SAD20/15-P-C6F	SAD20/15-V-C6F
S12*1	39 1.54	A	SAD20/12-P-C6F	SAD20/12-V-C6F
Plug in	37 1.46	B	SAD20/10-P-C6F	SAD20/10-V-C6F

Threads

*1 Special thread: buttress thread S12,65 x1,5


Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".


Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).



Gauge Adaptor SMA20



Direct Gauge Adaptor SMD20

Gauge Adaptor SMA20 Direct Gauge Adaptor SMD20



Thread	Dimensions (mm/in)		Order Codes NBR	FPM* (Standard Option-North America)
G	h	Hex A		
G1/4	54 2.13	19 .75	SMA20-G1/4-P-OR-C6F	SMA20-G1/4-V-OR-C6F
G1/2	64 2.52	27 1.06	SMA20-G1/2-P-OR-C6F	SMA20-G1/2-V-OR-C6F
1/4 NPT	54 2.13	19 .75	SMA20-1/4NPT-P-C6F	SMA20-1/4NPT-V-C6F
1/2 NPT	64 2.52	27 1.06	SMA20-1/2NPT-P-C6F	SMA20-1/2NPT-V-C6F
9/16-18 UNF	57 2.24	19 .75	SMA20-9/16UNF-P-C6F	SMA20-9/16UNF-V-C6F
G1/4	41 1.61	19 .75	SMD20-G1/4-P-OR-C6F	SMD20-G1/4-V-OR-C6F
G1/2	51 2.01	27 1.06	SMD20-G1/2-P-OR-C6F	SMD20-G1/2-V-OR-C6F
1/4 NPT	41 1.61	19 .75	SMD20-1/4NPT-P-C6F	SMD20-1/4NPT-V-C6F
1/2 NPT	51 2.01	27 1.06	SMD20-1/2NPT-P-C6F	SMD20-1/2NPT-V-C6F
7/16-20 UNF	41 1.61	19 .75	SMD20-7/16UNF-P-C6F	SMD20-7/16UNF-V-C6F

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".


Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Snubber on request.

Test Coupling with Piston Valve



Fast coupling for

- Monitoring and control of pressure
- Venting
- Sampling in high- and low-pressure systems
- Filling of accumulators (special filling-version)

Advantages

- Test system at working pressure
- Leakproof connection before **piston valve** is open
- Simple connection to measurement, control and switching devices
- Self locking metal protective cap

Working Pressure

- Max. working pressure 630 bar / 9137 PSI
For SKK Type G and K the recommended working pressure of fitting manufacturer should be noted.
- Connection under pressure up to 400 bar / 5801 PSI max.

DVGW

- DVGW registration as test coupling for gas pressure control systems with the Deutsche Vereinigung des Gas- und Wasserfaches e.V.
- The DVGW approval relates solely to the following test couplings:
 - SKK20-M8x1-VA-DVGW-C6F
 - SKK20-M10x1-VA-DVGW-C6F
 - SKK20-1/8NPT-VD-DVGW-C6F
 - SKK20-1/4NPT-VD-DVGW-C6F

Media

- Suitable for hydraulic oils and other Mineral oil based fluids
(Check compatibility of sealing material)
- For use with other liquid media please consult STAUFF
- In case of ultimate tightness requirements for gaseous media, a special Gas-type is available

Materials

▪ Metal Parts:

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**

Optional:

Stainless Steel **V2A** (1.4305 / AISI 303) on request

Stainless Steel **V4A** (1.4571 / AISI 316Ti) on request

For ordering "V2A" or "V4A" please replace "C6F" with "V2A" or "V4A".

▪ Sealings:

P = NBR (Buna-N®)

(Temperature range -20 °C ... +100 °C / -4 °F ... +212 °F)

Note: Internal sealings made of FPM, even for standard NBR-type.

V = FPM (Viton®)*

(Temperature range -20 °C ... +200 °C / -4 °F ... +392 °F)

*** Standard option for North America is FPM (Viton®)**

E = EPDM Ethylene Propylene Diene Monomer Rubber

(for Brake fluid,

Temperature range -40 °C ... +150 °C / -40 °F ... +302 °F)

For ordering NBR or EPDM sealings please replace "V" with "P" or "E".

Vibration safety O-ring made of NBR (Buna-N®) (standard).

Protection Cap

- The complete STAUFF-Test-20-Type-SKK range is also available with a hexagonal protection cap made of steel or plastic protection cap.

For ordering the hexagonal protection cap version please add "-SK" to the order code.
(e.g. SKK20-M10x1-VA-SK-C6F)

For ordering the plastic protection cap version please add "-KK" to the order code.
(e.g. SKK20-M10x1-VA-KK-C6F)

SKK20
Test Coupling
with Port Connection





SKK20 Type G
Test Coupling complete
with Straight Fitting



SKK20 Type K
Test Coupling for
24° Cone Fittings





Test Coupling with Port Connection SKK20



Thread G	Sealing	Working Pressure (^{bar} /psi)	Dimensions (^{mm} / ⁱⁿ)			Order Codes	
			h1	h2	Hex	NBR	FPM* (Standard Option-North America)
M8 x 1	Type A	250	38	8,5	17	SKK20-M8x1-PA-C6F	SKK20-M8x1-VA-C6F
		3625	1.50	.33	.67		
M10 x 1		630	38	9,8	17	SKK20-M10x1-PA-C6F	SKK20-M10x1-VA-C6F
		9137	1.50	.39	.67		
M12 x 1,5	Type B	630	37	12	17	SKK20-M12x1,5-PB-C6F	SKK20-M12x1,5-VB-C6F
		9137	1.46	.47	.67		
M14 x 1,5		630	37	12	19	SKK20-M14x1,5-PB-C6F	SKK20-M14x1,5-VB-C6F
		9137	1.46	.47	.75		
M16 x 1,5	Type B	630	37	12	22	SKK20-M16x1,5-PB-C6F	SKK20-M16x1,5-VB-C6F
		9137	1.46	.47	.87		
G1/4		630	37	12	19	SKK20-G1/4-PB-C6F	SKK20-G1/4-VB-C6F
		9137	1.46	.47	.75		
G3/8	Type C	630	37	12	22	SKK20-G3/8-PB-C6F	SKK20-G3/8-VB-C6F
		9137	1.46	.47	.87		
M10 x 1		400	39	8	17	SKK20-M10x1-PC-C6F	SKK20-M10x1-VC-C6F
		5801	1.54	.31	.67		
M12 x 1,5	Type C	630	37	12	17	SKK20-M12x1,5-PC-C6F	SKK20-M12x1,5-VC-C6F
		9137	1.46	.47	.67		
M14 x 1,5		630	37	12	19	SKK20-M14x1,5-PC-C6F	SKK20-M14x1,5-VC-C6F
		9137	1.46	.47	.75		
M16 x 1,5	Type C	630	37	12	22	SKK20-M16x1,5-PC-C6F	SKK20-M16x1,5-VC-C6F
		9137	1.46	.47	.87		
G1/8		400	39	8	17	SKK20-G1/8-PC-C6F	SKK20-G1/8-VC-C6F
		5801	1.54	.31	.67		
G1/4	Type C	630	37	12	19	SKK20-G1/4-PC-C6F	SKK20-G1/4-VC-C6F
		9137	1.46	.47	.75		
G3/8		630	37	12	22	SKK20-G3/8-PC-C6F	SKK20-G3/8-VC-C6F
		9137	1.46	.47	.87		
G1/2	Type D	630	39	14	27	SKK20-G1/2-PC-C6F	SKK20-G1/2-VC-C6F
		9137	1.54	.55	1.06		
R1/8 K		400	37	8	17	SKK20-R1/8K-PD-C6F	SKK20-R1/8K-VD-C6F
		5801	1.46	.31	.67		
R1/4 K	Type D	630	35	12	17	SKK20-R1/4K-PD-C6F	SKK20-R1/4K-VD-C6F
		9137	1.38	.47	.67		
1/8 NPT		400	36	10	17	SKK20-1/8NPT-PD-C6F	SKK20-1/8NPT-VD-C6F
		5801	1.42	.39	.67		
1/4 NPT	Type E	630	35	15	17	SKK20-1/4NPT-PD-C6F	SKK20-1/4NPT-VD-C6F
		9137	1.38	.59	.67		
5/16-24 UNF		400	38	7,5	17	SKK20-5/16UNF-PE-C6F	SKK20-5/16UNF-VE-C6F
		5801	1.50	.30	.67		
7/16-20 UNF	Type E	630	38	9,1	17	SKK20-7/16UNF-PE-C6F	SKK20-7/16UNF-VE-C6F
		9137	1.50	.36	.67		
1/2-20 UNF		630	38	9,2	17	SKK20-1/2UNF-PE-C6F	SKK20-1/2UNF-VE-C6F
		9137	1.50	.36	.67		
9/16-18 UNF	Type E	630	37	10	19	SKK20-9/16UNF-PE-C6F	SKK20-9/16UNF-VE-C6F
		9137	1.46	.39	.75		
M12 x 1,5		630	37	11	17	SKK20-M12x1,5-PE-C6F	SKK20-M12x1,5-VE-C6F
		9137	1.46	.43	.67		
M14 x 1,5	Type E	630	38	11	19	SKK20-M14x1,5-PE-C6F	SKK20-M14x1,5-VE-C6F
		9137	1.50	.43	.75		

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Sealing Details



O-ring Type A



Metal Joint Type B



Elastomeric Sealing Type C



Taper Type D
(suitable sealant required)



O-ring Type E


Protection Cap

Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SKK20-M10x1-VA-SK-C6F)
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SKK20-M10x1-VA-KK-C6F)

For further information on materials, sealings or protection caps, please see page B12.

Other port connections and sealings on request.
Please consult STAUFF for further information.

Test Coupling complete with Straight Fitting SKK20 Type G



- Compression ring fittings acc. to ISO 8434-1 / DIN 2353

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".


* Standard option for North America is FPM (Viton®).

Protection Cap


Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SKK20-08L-VG-SK-C6F)
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SKK20-08L-VG-KK-C6F)

For further information on materials, sealings or protection caps, please see page B12.

Series	PN (^{bar} /PS)	Pipe Ød	Dimensions (^{mm} / ⁱⁿ)						Order Codes	
			~I1	I2	h	Hex A	Hex B		NBR	FPM* (Standard Option-North America)
L	315 4568	6	51 2.01	21 .83	49 1.93	24 .94	14 .55		SKK20-06L-PG-C6F	SKK20-06L-VG-C6F
		8	51 2.01	21 .83	49 1.93	24 .94	17 .67		SKK20-08L-PG-C6F	SKK20-08L-VG-C6F
		10	53 2.09	23 .91	49 1.93	24 .94	19 .75		SKK20-10L-PG-C6F	SKK20-10L-VG-C6F
		12	53 2.09	23 .91	50,5 1.99	27 1.06	22 .87		SKK20-12L-PG-C6F	SKK20-12L-VG-C6F
		15	55 2.17	25 .98	52 2.05	30 1.18	27 1.06		SKK20-15L-PG-C6F	SKK20-15L-VG-C6F
		18	57 2.24	24 .94	53 2.09	32 1.26	32 1.26		SKK20-18L-PG-C6F	SKK20-18L-VG-C6F
	160 2320	22	61 2.40	28 1.10	55 2.17	36 1.42	36 1.42		SKK20-22L-PG-C6F	SKK20-22L-VG-C6F
		28	61 2.40	28 1.10	57,5 2.26	41 1.61	41 1.61		SKK20-28L-PG-C6F	SKK20-28L-VG-C6F
		35	69 2.72	26 1.02	60 2.36	46 1.81	50 1.97		SKK20-35L-PG-C6F	SKK20-35L-VG-C6F
		42	71 2.80	25 .98	64,5 2.54	55 2.17	60 2.36		SKK20-42L-PG-C6F	SKK20-42L-VG-C6F
	S	6	55 2.17	25 .98	49 1.93	24 .94	17 .67		SKK20-06S-PG-C6F	SKK20-06S-VG-C6F
		8	55 2.17	25 .98	49 1.93	24 .94	19 .75		SKK20-08S-PG-C6F	SKK20-08S-VG-C6F
		10	57 2.24	24 .94	49 1.93	24 .94	22 .87		SKK20-10S-PG-C6F	SKK20-10S-VG-C6F
		12	57 2.24	24 .94	49 1.93	24 .94	24 .94		SKK20-12S-PG-C6F	SKK20-12S-VG-C6F
		14	63 2.50	27 1.06	50,5 1.99	27 1.06	27 1.06		SKK20-14S-PG-C6F	SKK20-14S-VG-C6F
		16	63 2.50	26 1.02	52 2.05	30 1.18	30 1.18		SKK20-16S-PG-C6F	SKK20-16S-VG-C6F
		20	69 2.72	26 1.02	55 2.17	36 1.42	36 1.42		SKK20-20S-PG-C6F	SKK20-20S-VG-C6F
		25	75 2.95	27 1.06	57,5 2.26	41 1.61	46 1.81		SKK20-25S-PG-C6F	SKK20-25S-VG-C6F
		30	81 3.19	28 1.10	60 2.36	46 1.81	50 1.97		SKK20-30S-PG-C6F	SKK20-30S-VG-C6F
		38	91 3.58	29 1.14	64,5 2.54	55 2.17	60 2.36		SKK20-38S-PG-C6F	SKK20-38S-VG-C6F



Version A



Version B

Test Coupling for 24° Cone Fittings SKK20 Type K



Series	PN (bar/psi)	Pipe Ød	Dimensions (mm/in)			Thread	Version	Order Codes	
			I3	Hex A	G			NBR	FPM* (Standard Option-North America)
L	315 4568	6	15,5 .61	14 .55	M12 x 1,5	A		SKK20-06L-PK-C6F	SKK20-06L-VK-C6F
		8	15,5 .61	17 .67	M14 x 1,5	A		SKK20-08L-PK-C6F	SKK20-08L-VK-C6F
		10	16,5 .65	19 .75	M16 x 1,5	A		SKK20-10L-PK-C6F	SKK20-10L-VK-C6F
		12	17,5 .69	22 .87	M18 x 1,5	A		SKK20-12L-PK-C6F	SKK20-12L-VK-C6F
		15	21 .83	27 1.06	M22 x 1,5	B		SKK20-15L-PK-GS-C6F	SKK20-15L-VK-GS-C6F
		18	19,5 .77	32 1.26	M26 x 1,5	B		SKK20-18L-PK-GS-C6F	SKK20-18L-VK-GS-C6F
	160 2320	22	20,5 .81	36 1.42	M30 x 2	B		SKK20-22L-PK-GS-C6F	SKK20-22L-VK-GS-C6F
		28	25 .98	41 1.61	M36 x 2	B		SKK20-28L-PK-GS-C6F	SKK20-28L-VK-GS-C6F
		35	30 1.18	50 1.97	M45 x 2	B		SKK20-35L-PK-GS-C6F	SKK20-35L-VK-GS-C6F
		42	31 1.22	60 2.36	M52 x 2	B		SKK20-42L-PK-GS-C6F	SKK20-42L-VK-GS-C6F
S	630 9137	6	14,5 .57	17 .67	M14 x 1,5	A		SKK20-06S-PK-C6F	SKK20-06S-VK-C6F
		8	16,5 .65	19 .75	M16 x 1,5	A		SKK20-08S-PK-C6F	SKK20-08S-VK-C6F
		10	16,5 .65	22 .87	M18 x 1,5	A		SKK20-10S-PK-C6F	SKK20-10S-VK-C6F
		12	17,5 .69	24 .94	M20 x 1,5	A		SKK20-12S-PK-C6F	SKK20-12S-VK-C6F
		14	19,5 .77	27 1.06	M22 x 1,5	B		SKK20-14S-PK-GS-C6F	SKK20-14S-VK-GS-C6F
	400 5801	16	18 .71	30 1.18	M24 x 1,5	B		SKK20-16S-PK-GS-C6F	SKK20-16S-VK-GS-C6F
		20	24 .94	36 1.42	M30 x 2	B		SKK20-20S-PK-GS-C6F	SKK20-20S-VK-GS-C6F
		25	26 1.02	46 1.81	M36 x 2	B		SKK20-25S-PK-GS-C6F	SKK20-25S-VK-GS-C6F
		30	30 1.18	50 1.97	M42 x 2	B		SKK20-30S-PK-GS-C6F	SKK20-30S-VK-GS-C6F
	315 4568	38	34 1.34	60 2.36	M52 x 2	B		SKK20-38S-PK-GS-C6F	SKK20-38S-VK-GS-C6F

- For DKO connection
- According to ISO 8434-1 / DIN 2353
- Version A: one-piece design
- Version B: screwed design

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".


* Standard option for North America is FPM (Viton®).

Protection Cap

Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SKK20-08L-VK-SK-C6F)
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SKK20-08L-VK-KK-C6F)

For further information on materials, sealings or protection caps, please see page B12.

Test Coupling with Ball Check



Fast coupling for

- Monitoring and control of pressure
- Venting
- Sampling in high- and low-pressure systems

Advantages

- Test system at working pressure
- Leak proof connection before **ball check** is open
- Simple connection to measurement, control and switching devices
- Self locking metal protective cap

Working Pressure

- Max. working pressure 630 bar / 9137 PSI
For SMK Type G and K the recommended working pressure of fitting manufacturer should be noted.
- Connection under pressure up to 630 bar / 9137 PSI max.

Materials

- **Metal parts:**
Standard material: Steel, black zinc/nickel-plated = **C6F*** (CrVI-free)
Optional:
Stainless Steel **V2A** (1.4305 / AISI 303) on request
Stainless Steel **V4A** (1.4571 / AISI 316Ti) on request

For ordering V2A or V4A please replace "C6F" with "V2A" or "V4A".

* Note: The changeover of our standard surface finishing "zinc plated" to the chromium (VI) free surface finishing "black zinc/nickel-plated" will proceed gradually.

- **Ball:** Stainless Steel

Sealings:

P = NBR (Buna-N®)

(Temperature range -20 °C ... +100 °C / -4 °F ... +212 °F)

Note: Internal sealings made of FPM, even for standard NBR-type.

V = FPM (Viton®)*

(Temperature range -20 °C ... +200 °C / -4 °F ... +392 °F)

*** Standard option for North America is FPM (Viton®)**

E = EPDM Ethylene Propylene Diene Monomer Rubber

(for Brake fluid,

Temperature range -40 °C ... +150 °C / -40 °F ... +302 °F)

For ordering NBR or EPDM sealings please replace "V" with "P" or "E".

Vibration safety O-ring made of NBR (Buna-N®) (standard).

Media

- Suitable for hydraulic oils and other Mineral oil based fluid
(Check compatibility of seal material)
- For use with other liquid media please consult STAUFF

Protection Cap



- The complete STAUFF-Test-15-Type-SMK range is also available with a hexagonal protection cap made of steel.

For ordering the hexagonal protection cap version please add "-SK" to the order code.
(e.g. SMK15-M10x1-VA-SK-C6F)

Note

- On request TEST 15 is also available as SKK-type including "Gas"- and "Filling"-versions.

SMK15 Test Coupling with Port Connection	SMK15 Type G Test Coupling complete with Straight Fitting	SMK15 Type K Test Coupling for 24° Cone Fittings	SSK15 Bulkhead
			



Test Coupling with Port Connection SMK15



Thread G	Sealing	Working Pressure (bar / psi)	Dimensions (mm / in)			Order Codes	
			h1	h2	Hex	NBR	FPM* (Standard Option-North America)
M10 x 1	Type A	630	38	9,8	17	SMK15-M10x1-PA-C6F	SMK15-M10x1-VA-C6F
		9137	1.50	.39	.67		
M14 x 1,5		630	37	12	19	SMK15-M14x1,5-PB-C6F	SMK15-M14x1,5-VB-C6F
		9137	1.46	.47	.75		
M16 x 1,5		630	37	12	22	SMK15-M16x1,5-PB-C6F	SMK15-M16x1,5-VB-C6F
		9137	1.46	.47	.87		
G1/8	Type B	400	39	8	17	SMK15-G1/8-PB-C6F	SMK15-G1/8-VB-C6F
		5801	1.54	.31	.67		
G1/4		630	37	12	19	SMK15-G1/4-PB-C6F	SMK15-G1/4-VB-C6F
		9137	1.46	.47	.75		
G3/8		630	37	12	22	SMK15-G3/8-PB-C6F	SMK15-G3/8-VB-C6F
		9137	1.46	.47	.87		
M12 x 1,5		630	37	12	17	SMK15-M12x1,5-PC-C6F	SMK15-M12x1,5-VC-C6F
		9137	1.46	.47	.67		
M14 x 1,5		630	37	12	19	SMK15-M14x1,5-PC-C6F	SMK15-M14x1,5-VC-C6F
		9137	1.46	.47	.75		
M16 x 1,5	Type C	630	37	12	22	SMK15-M16x1,5-PC-C6F	SMK15-M16x1,5-VC-C6F
		9137	1.46	.47	.87		
G1/8		400	39	8	17	SMK15-G1/8-PC-C6F	SMK15-G1/8-VC-C6F
		5801	1.54	.31	.67		
G1/4		630	37	12	19	SMK15-G1/4-PC-C6F	SMK15-G1/4-VC-C6F
		9137	1.46	.47	.75		
R1/4 K		630	35	12	17	SMK15-R1/4K-PD-C6F	SMK15-R1/4K-VD-C6F
		9137	1.38	.47	.67		
1/8 NPT	Type D	400	36	10	17	SMK15-1/8NPT-PD-C6F	SMK15-1/8NPT-VD-C6F
		5801	1.42	.39	.67		
1/4 NPT		630	35	15	17	SMK15-1/4NPT-PD-C6F	SMK15-1/4NPT-VD-C6F
		9137	1.38	.59	.67		
7/16-20 UNF		630	38	9,1	17	SMK15-7/16UNF-PE-C6F	SMK15-7/16UNF-VE-C6F
		9137	1.50	.36	.67		
9/16-18 UNF	Type E	630	37	10	19	SMK15-9/16UNF-PE-C6F	SMK15-9/16UNF-VE-C6F
		9137	1.46	.39	.75		
M14 x 1,5		630	38	11	19	SMK15-M14x1,5-PE-C6F	SMK15-M14x1,5-VE-C6F
		9137	1.50	.43	.75		

Metal Parts

Standard material:
Steel, black zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Sealing Details



O-ring Type A



Metal Joint Type B



Elastomeric Sealing Type C



Taper Type D
(suitable sealant required)



O-ring Type E


Protection Cap

Standard material: Steel
For ordering the hexagonal protection cap version please add
"-SK" to the order code. (e.g. SMK15-M10x1-VA-SK-C6F)

For further information on materials, seals or protection caps,
please see page B16.

Other port connections and seals on request.
Please consult STAUFF for further information.

Test Coupling complete with Straight Fitting SMK15 Type G



- Compression ring fittings acc. to ISO 8434-1 / DIN 2353

Metal Parts

Standard material:

- Test coupling:
Steel, black zinc/nickel-plated = **C6F (CrVI-free)**
- Straight fitting: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".

For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Protection Cap


Standard material: Steel

For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SMK15-08L-VG-SK-C6F)


For further information on materials, sealings or protection caps, please see page B16.

Series	PN (bar/psi)	Pipe	Dimensions (mm/in)						Order Codes	
		Ød	~I1	I2	h	Hex A	Hex B		NBR	FPM* (Standard Option-North America)
L	315 4568	6	51 2.01	21 .83	49 1.93	24 .94	14 .55		SMK15-06L-PG-C6F	SMK15-06L-VG-C6F
		8	51 2.01	21 .83	49 1.93	24 .94	17 .67		SMK15-08L-PG-C6F	SMK15-08L-VG-C6F
		10	53 2.09	23 .91	49 1.93	24 .94	19 .75		SMK15-10L-PG-C6F	SMK15-10L-VG-C6F
		12	53 2.09	23 .91	50,5 1.99	27 1.06	22 .87		SMK15-12L-PG-C6F	SMK15-12L-VG-C6F
		15	55 2.17	25 .98	52 2.05	30 1.18	27 1.06		SMK15-15L-PG-C6F	SMK15-15L-VG-C6F
		18	57 2.24	24 .94	53 2.09	32 1.26	32 1.26		SMK15-18L-PG-C6F	SMK15-18L-VG-C6F
	160 2320	22	61 2.40	28 1.10	55 2.17	36 1.42	36 1.42		SMK15-22L-PG-C6F	SMK15-22L-VG-C6F
		28	61 2.40	28 1.10	57,5 2.26	41 1.61	41 1.61		SMK15-28L-PG-C6F	SMK15-28L-VG-C6F
		35	69 2.72	26 1.02	60 2.36	46 1.81	50 1.97		SMK15-35L-PG-C6F	SMK15-35L-VG-C6F
		42	71 2.80	25 .98	64,5 2.54	55 2.17	60 2.36		SMK15-42L-PG-C6F	SMK15-42L-VG-C6F
	S	6	55 2.17	25 .98	49 1.93	24 .94	17 .67		SMK15-06S-PG-C6F	SMK15-06S-VG-C6F
		8	55 2.17	25 .98	49 1.93	24 .94	19 .75		SMK15-08S-PG-C6F	SMK15-08S-VG-C6F
		10	57 2.24	24 .94	49 1.93	24 .94	22 .87		SMK15-10S-PG-C6F	SMK15-10S-VG-C6F
		12	57 2.24	24 .94	49 1.93	24 .94	24 .94		SMK15-12S-PG-C6F	SMK15-12S-VG-C6F
		14	63 2.50	27 1.06	50,5 1.99	27 1.06	27 1.06		SMK15-14S-PG-C6F	SMK15-14S-VG-C6F
		16	63 2.50	26 1.02	52 2.05	30 1.18	30 1.18		SMK15-16S-PG-C6F	SMK15-16S-VG-C6F
		20	69 2.72	26 1.02	55 2.17	36 1.42	36 1.42		SMK15-20S-PG-C6F	SMK15-20S-VG-C6F
		25	75 2.95	27 1.06	57,5 2.26	41 1.61	46 1.81		SMK15-25S-PG-C6F	SMK15-25S-VG-C6F
		30	81 3.19	28 1.10	60 2.36	46 1.81	50 1.97		SMK15-30S-PG-C6F	SMK15-30S-VG-C6F
	315 4568	38	91 3.58	29 1.14	64,5 2.54	55 2.17	60 2.36		SMK15-38S-PG-C6F	SMK15-38S-VG-C6F

Test Coupling for 24° Cone Fittings SMK15 Type K



Version A



Version B



Series	PN (^{ns/ps})	Pipe Ød	Dimensions (^{mm} / ⁱⁿ)			Thread	Version	Order Codes	
			I3	Hex A	G			NBR	FPM* (Standard Option-North America)
L	315 4568	6	15,5 .61	14 .55	M12 x 1,5	A		SMK15-06L-PK-C6F	SMK15-06L-VK-C6F
		8	15,5 .61	17 .67	M14 x 1,5	A		SMK15-08L-PK-C6F	SMK15-08L-VK-C6F
		10	16,5 .65	19 .75	M16 x 1,5	A		SMK15-10L-PK-C6F	SMK15-10L-VK-C6F
		12	17,5 .69	22 .87	M18 x 1,5	A		SMK15-12L-PK-C6F	SMK15-12L-VK-C6F
		15	21 .83	27 1.06	M22 x 1,5	B		SMK15-15L-PK-GS-C6F	SMK15-15L-VK-GS-C6F
		18	19,5 .77	32 1.26	M26 x 1,5	B		SMK15-18L-PK-GS-C6F	SMK15-18L-VK-GS-C6F
	160 2320	22	20,5 .81	36 1.42	M30 x 2	B		SMK15-22L-PK-GS-C6F	SMK15-22L-VK-GS-C6F
		28	25 .98	41 1.61	M36 x 2	B		SMK15-28L-PK-GS-C6F	SMK15-28L-VK-GS-C6F
		35	30 1.18	50 1.97	M45 x 2	B		SMK15-35L-PK-GS-C6F	SMK15-35L-VK-GS-C6F
		42	31 1.22	60 2.36	M52 x 2	B		SMK15-42L-PK-GS-C6F	SMK15-42L-VK-GS-C6F
S	630 9137	6	14,5 .57	17 .67	M14 x 1,5	A		SMK15-06S-PK-C6F	SMK15-06S-VK-C6F
		8	16,5 .65	19 .75	M16 x 1,5	A		SMK15-08S-PK-C6F	SMK15-08S-VK-C6F
		10	16,5 .65	22 .87	M18 x 1,5	A		SMK15-10S-PK-C6F	SMK15-10S-VK-C6F
		12	17,5 .69	24 .94	M20 x 1,5	A		SMK15-12S-PK-C6F	SMK15-12S-VK-C6F
		14	19,5 .77	27 1.06	M22 x 1,5	B		SMK15-14S-PK-GS-C6F	SMK15-14S-VK-GS-C6F
	400 5801	16	18 .71	30 1.18	M24 x 1,5	B		SMK15-16S-PK-GS-C6F	SMK15-16S-VK-GS-C6F
		20	24 .94	36 1.42	M30 x 2	B		SMK15-20S-PK-GS-C6F	SMK15-20S-VK-GS-C6F
		25	26 1.02	46 1.81	M36 x 2	B		SMK15-25S-PK-GS-C6F	SMK15-25S-VK-GS-C6F
		30	30 1.18	50 1.97	M42 x 2	B		SMK15-30S-PK-GS-C6F	SMK15-30S-VK-GS-C6F
	315 4568	38	34 1.34	60 2.36	M52 x 2	B		SMK15-38S-PK-GS-C6F	SMK15-38S-VK-GS-C6F

- For DKO connection
- According to ISO 8434-1 / DIN 2353
- Version A: one-piece design
- Version B: screwed design

Metal Parts

Standard material:

- Test coupling: Steel, black zinc/nickel-plated = **C6F (CrVI-free)**
- 24° cone fittings: Steel, zinc/nickel-plated = C6F (CrVI-free)
- For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
- For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".


* Standard option for North America is FPM (Viton®).

Protection Cap


Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SMK15-08L-VK-SK-C6F)

For further information on materials, sealings or protection caps, please see page B16.

Bulkhead SSK15



Version A



Version B

- Also available for gaseous media type SSKK

Threads

*1 Compression ring assembly 08S according to ISO 8434-1 / DIN 2353

Metal Parts

Standard material version A:

- Test coupling:
Steel, black zinc/nickel-plated = **C6F (CrVI-free)**

Standard material version B:

- Test coupling:
Steel, black zinc/nickel-plated = **C6F (CrVI-free)**
 - Hex nut: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
- For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).


Protection Cap


Standard material: Steel
For ordering the hexagonal protection cap version please add "-SK" to the order code. (e.g. SSK15-V-SK-C6F)

For further information on materials, sealings or protection caps, please see page B16.


Note: Standard option version B without compression ring and nut.

Swivel Run Tee with JIC Connection SGV-JIC Type F/M





Version A



Version B

Adaptor SAD15



Thread	Dimensions (mm/in)	Version	Order Codes NBR	FPM* (Standard Option-North America)
G	h			
M16 x 2	39 1.54	A	SAD15/20-P-C6F	SAD15/20-V-C6F
S12 *1	39 1.54	A	SAD15/12-P-C6F	SAD15/12-V-C6F
Plug in	37 1.46	B	SAD15/10-P-C6F	SAD15/10-V-C6F

Threads

*1 Special thread: buttress thread S12,65 x1,5

Metal Parts

Standard material version A:

- Threaded nipple: Steel, black zinc/nickel-plated = **C6F (CrVI-free)**
- Swivel nut: Steel, zinc/nickel-plated = **C6F (CrVI-free)**

Standard material version B:

Steel, black zinc/nickel-plated = **C6F (CrVI-free)**

For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".


For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings


For ordering NBR sealings replace "V" with "P".

For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).



Gauge Adaptor SMA15



Direct Gauge Adaptor SMD15

Gauge Adaptor SMA15 Direct Gauge Adaptor SMD15



Thread	Dimensions (mm/in)	Hex A	Order Codes NBR	FPM* (Standard Option-North America)
G	h			
G1/4	54 2.13	19 .75	SMA15-G1/4-P-OR-C6F	SMA15-G1/4-V-OR-C6F
G1/2	64 2.52	27 1.06	SMA15-G1/2-P-OR-C6F	SMA15-G1/2-V-OR-C6F
1/4 NPT	54 2.13	19 .75	SMA15-1/4NPT-P-C6F	SMA15-1/4NPT-V-C6F
1/2 NPT	64 2.52	27 1.06	SMA15-1/2NPT-P-C6F	SMA15-1/2NPT-V-C6F
G1/4	41 1.61	19 .75	SMD15-G1/4-P-OR-C6F	SMD15-G1/4-V-OR-C6F
G1/2	51 2.01	27 1.06	SMD15-G1/2-P-OR-C6F	SMD15-G1/2-V-OR-C6F
1/4 NPT	41 1.61	19 .75	SMD15-1/4NPT-P-C6F	SMD15-1/4NPT-V-C6F
1/2 NPT	51 2.01	27 1.06	SMD15-1/2NPT-P-C6F	SMD15-1/2NPT-V-C6F

Metal Parts

Standard material SMA15:

Steel, black zinc/nickel-plated = **C6F (CrVI-free)**

Standard material SMD15:

- Gauge adaptor: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
- Swivel nut: Steel, black zinc/nickel-plated = **C6F (CrVI-free)**

For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".

For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings


For ordering NBR sealings replace "V" with "P".

For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Snubber on request.

Test Coupling with Piston Valve



Fast Coupling for

- Monitoring and control of pressure
- Venting
- Sampling in high- and low-pressure systems
- Filling of accumulators (special filling-version)

Advantages

- Test system at working pressure
- Leak proof connection before **piston valve** is open
- Simple connection to measurement, control and switching devices
- Self locking metal protective cap

Working Pressure

- Max. working pressure 630 bar / 9137 PSI
For SKK Type G and K the recommended working pressure of fitting manufacturer should be noted.
- Connection under pressure up to 400 bar / 5801 PSI max.

Materials

- Metal Parts:**
Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
Optional:
Stainless Steel **V2A** (1.4305 / AISI 303) on request
Stainless Steel **V4A** (1.4571 / AISI 316Ti) on request

For ordering "V2A" or "V4A" please replace "C6F" with "V2A" or "V4A".

Sealings:

P = NBR (Buna-N®)

(Temperature range -20 °C ... +100 °C / -4 °F ... +212 °F)

Note: Internal sealings made of FPM, even for standard NBR-type.

V = FPM (Viton®)*

(Temperature range -20 °C ... +200 °C / -4 °F ... +392 °F)

*** Standard option for North America is FPM (Viton®)**

E = EPDM Ethylene Propylene Diene Monomer Rubber
(for Brake fluid,
Temperature range -40 °C ... +150 °C / -40 °F ... +302 °F)

For ordering NBR or EPDM sealings please replace "V" with "P" or "E".

Vibration safety O-ring made of NBR (Buna-N®) (standard).

Media



- Suitable for hydraulic oils and other Mineral oil based fluids
(Check compatibility of seal material)
- For use with other liquid media please consult STAUFF
- In case of ultimate tightness requirements for gaseous media, a special Gas-type is available

Protection Cap

- The complete STAUFF-Test-12-type-SKK range is also available with a plastic protection cap.

For ordering the plastic protection cap version please add "-KK" to the order code.
(e.g. SKK12-M10x1-VA-KK-C6F)

SKK12 Test Coupling with Port Connection	SKK12 Type G Test Coupling complete with Straight Fitting	SKK12 Type K Test Coupling for 24° Cone Fittings	SSKK12 Bulkhead
			



Test Coupling with Port Connection SKK12



Thread	Sealing	Working Pressure (bar / psi)	Dimensions (mm / in)			Order Codes		
G			h1	h2	Hex	NBR	FPM* (Standard Option-North America)	
M8 x 1	Type A	250	38	8,5	14	SKK12-M8x1-PA-C6F	SKK12-M8x1-VA-C6F	
		3625	1.50	.33	.55			
M10 x 1		630	35	9,8	14	SKK12-M10x1-PA-C6F	SKK12-M10x1-VA-C6F	
		9137	1.38	.39	.67			
M12 x 1,5	Type B	630	31	12	17	SKK12-M12x1,5-PB-C6F	SKK12-M12x1,5-VB-C6F	
9137		1.22	.47	.67				
M14 x 1,5		630	31	12	19	SKK12-M14x1,5-PB-C6F	SKK12-M14x1,5-VB-C6F	
		9137	1.22	.47	.75			
M16 x 1,5		630	31	12	22	SKK12-M16x1,5-PB-C6F	SKK12-M16x1,5-VB-C6F	
		9137	1.22	.47	.87			
G1/4		630	30	12	19	SKK12-G1/4-PB-C6F	SKK12-G1/4-VB-C6F	
		9137	1.18	.47	.75			
G3/8		630	31	12	22	SKK12-G3/8-PB-C6F	SKK12-G3/8-VB-C6F	
		9137	1.22	.47	.87			
M12 x 1,5		Type C	630	31	12	17	SKK12-M12x1,5-PC-C6F	SKK12-M12x1,5-VC-C6F
			9137	1.22	.47	.67		
G1/8	400		40	8	14	SKK12-G1/8-PC-C6F	SKK12-G1/8-VC-C6F	
	5801		1.57	.31	.55			
G1/4	630		31	12	19	SKK12-G1/4-PC-C6F	SKK12-G1/4-VC-C6F	
	9137		1.22	.47	.75			
R1/8 K	Type D		400	33	8	17	SKK12-R1/8K-PD-C6F	SKK12-R1/8K-VD-C6F
			5801	1.30	.31	.55		
R1/4 K		630	30	12	17	SKK12-R1/4K-PD-C6F	SKK12-R1/4K-VD-C6F	
		9137	1.18	.47	.55			
1/8 NPT		400	33	10	14	SKK12-1/8NPT-PD-C6F	SKK12-1/8NPT-VD-C6F	
		5801	1.30	.39	.55			
1/4 NPT		630	28	15	14	SKK12-1/4NPT-PD-C6F	SKK12-1/4NPT-VD-C6F	
		9137	1.10	.59	.55			
5/16-24 UNF	Type E	400	38	7,5	14	SKK12-5/16UNF-PE-C6F	SKK12-5/16UNF-VE-C6F	
		5801	1.50	.30	.55			
7/16-20 UNF		630	33	9,1	17	SKK12-7/16UNF-PE-C6F	SKK12-7/16UNF-VE-C6F	
		9137	1.30	.36	.67			
1/2-20 UNF		630	32	9,2	17	SKK12-1/2UNF-PE-C6F	SKK12-1/2UNF-VE-C6F	
		9137	1.26	.36	.67			
9/16-18 UNF		630	31	10	19	SKK12-9/16UNF-PE-C6F	SKK12-9/16UNF-VE-C6F	
		9137	1.22	.39	.75			
M12 x1,5		630	32	11	17	SKK12-M12x1,5-PE-C6F	SKK12-M12x1,5-VE-C6F	
		9137	1.26	.43	.67			

Threads

*1 Special thread: buttress thread S12,65 x 1,5

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Sealing Details



O-ring Type A



Metal Joint Type B



Elastomeric Sealing Type C



Taper Type D
(suitable sealant required)



O-ring Type E

Protection Cap


Standard material: Steel

For ordering the plastic protection cap version please add
"-KK" to the order code. (e.g. SKK12-M10x1-VA-KK-C6F)

For further information on materials, sealings or protection
caps, please see page B22.

Other port connections and sealings on request.
Please consult STAUFF for further information.

Test Coupling complete with Straight Fitting SKK12 Type G



- Compression ring fittings acc. to ISO 8434-1 / DIN 2353

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".


* Standard option for North America is FPM (Viton®).

Protection Cap


Standard material: Steel
For ordering the plastic protection cap version please add
"-KK" to the order code. (e.g. SKK12-06L-VG-KK-C6F)

For further information on materials, sealings or protection caps, please see page B22.

Series	PN (^{bar} /PS)	Pipe Ød	Dimensions (mm/in)						Order Codes	
			~l1	l2	h	Hex A	Hex B		NBR	FPM* (Standard Option-North America)
L	315 4568	6	51 2.01	21 .83	46 1.81	24 .94	14 .55		SKK12-06L-PG-C6F	SKK12-06L-VG-C6F
		8	51 2.01	21 .83	46 1.81	24 .94	17 .67		SKK12-08L-PG-C6F	SKK12-08L-VG-C6F
		10	53 2.09	23 .91	46 1.81	24 .94	19 .75		SKK12-10L-PG-C6F	SKK12-10L-VG-C6F
		12	53 2.09	23 .91	47,5 1.87	27 1.06	22 .87		SKK12-12L-PG-C6F	SKK12-12L-VG-C6F
		15	55 2.17	25 .98	49 1.92	30 1.18	27 1.06		SKK12-15L-PG-C6F	SKK12-15L-VG-C6F
		18	57 2.24	24 .94	50 1.97	32 1.26	32 1.26		SKK12-18L-PG-C6F	SKK12-18L-VG-C6F
	160 2320	22	61 2.40	28 1.10	52 2.05	36 1.42	36 1.42		SKK12-22L-PG-C6F	SKK12-22L-VG-C6F
		28	61 2.40	28 1.10	54,5 2.15	41 1.61	41 1.61		SKK12-28L-PG-C6F	SKK12-28L-VG-C6F
		35	69 2.72	26 1.02	57 2.24	46 1.81	50 1.97		SKK12-35L-PG-C6F	SKK12-35L-VG-C6F
		42	71 2.80	25 .98	61,5 2.42	55 2.17	60 2.36		SKK12-42L-PG-C6F	SKK12-42L-VG-C6F
S	630 9137	6	55 2.17	25 .98	46 1.81	24 .94	17 .67		SKK12-06S-PG-C6F	SKK12-06S-VG-C6F
		8	55 2.17	25 .98	46 1.81	24 .94	19 .75		SKK12-08S-PG-C6F	SKK12-08S-VG-C6F
		10	57 2.24	24 .94	46 1.81	24 .94	22 .87		SKK12-10S-PG-C6F	SKK12-10S-VG-C6F
		12	57 2.24	24 .94	46 1.81	24 .94	24 .94		SKK12-12S-PG-C6F	SKK12-12S-VG-C6F
		14	63 2.50	27 1.06	47,5 1.87	27 1.06	27 1.06		SKK12-14S-PG-C6F	SKK12-14S-VG-C6F
	400 5801	16	63 2.50	26 1.02	49 1.93	30 1.18	30 1.18		SKK12-16S-PG-C6F	SKK12-16S-VG-C6F
		20	69 2.72	26 1.02	52 2.05	36 1.42	36 1.42		SKK12-20S-PG-C6F	SKK12-20S-VG-C6F
		25	75 2.95	27 1.06	54,5 2.15	41 1.61	46 1.81		SKK12-25S-PG-C6F	SKK12-25S-VG-C6F
		30	81 3.19	28 1.10	57 2.24	46 1.81	50 1.97		SKK12-30S-PG-C6F	SKK12-30S-VG-C6F
		38	91 3.58	29 1.14	61,5 2.42	55 2.17	60 2.36		SKK12-38S-PG-C6F	SKK12-38S-VG-C6F



Version A



Version B

Test Coupling for 24° Cone Fittings SKK12 Type K



Series	PN (bar/psi)	Pipe Ød	Dimensions (mm/in)		Thread G	Version	Order Codes	
			I3	Hex A			NBR	FPM* (Standard Option-North America)
L	315 4568	6	15,5 .61	14 .55	M12 x 1,5	A	SKK12-06L-PK-C6F	SKK12-06L-VK-C6F
		8	15,5 .61	17 .67	M14 x 1,5	A	SKK12-08L-PK-C6F	SKK12-08L-VK-C6F
		10	16,5 .65	19 .75	M16 x 1,5	A	SKK12-10L-PK-C6F	SKK12-10L-VK-C6F
		12	17,5 .69	22 .87	M18 x 1,5	A	SKK12-12L-PK-C6F	SKK12-12L-VK-C6F
		15	21 .83	27 1.06	M22 x 1,5	B	SKK12-15L-PK-GS-C6F	SKK12-15L-VK-GS-C6F
		18	19,5 .77	32 1.26	M26 x 1,5	B	SKK12-18L-PK-GS-C6F	SKK12-18L-VK-GS-C6F
	160 2320	22	20,5 .81	36 1.42	M30 x 2	B	SKK12-22L-PK-GS-C6F	SKK12-22L-VK-GS-C6F
		28	25 .98	41 1.61	M36 x 2	B	SKK12-28L-PK-GS-C6F	SKK12-28L-VK-GS-C6F
		35	30 1.18	50 1.97	M45 x 2	B	SKK12-35L-PK-GS-C6F	SKK12-35L-VK-GS-C6F
		42	31 1.22	60 2.36	M52 x 2	B	SKK12-42L-PK-GS-C6F	SKK12-42L-VK-GS-C6F
S	630 9137	6	14,5 .57	17 .67	M14 x 1,5	A	SKK12-06S-PK-C6F	SKK12-06S-VK-C6F
		8	16,5 .65	19 .75	M16 x 1,5	A	SKK12-08S-PK-C6F	SKK12-08S-VK-C6F
		10	16,5 .65	22 .87	M18 x 1,5	A	SKK12-10S-PK-C6F	SKK12-10S-VK-C6F
		12	17,5 .69	24 .94	M20 x 1,5	A	SKK12-12S-PK-C6F	SKK12-12S-VK-C6F
		14	19,5 .77	27 1.06	M22 x 1,5	B	SKK12-14S-PK-GS-C6F	SKK12-14S-VK-GS-C6F
	400 5801	16	18 .71	30 1.18	M24 x 1,5	B	SKK12-16S-PK-GS-C6F	SKK12-16S-VK-GS-C6F
		20	24 .94	36 1.42	M30 x 2	B	SKK12-20S-PK-GS-C6F	SKK12-20S-VK-GS-C6F
		25	26 1.02	46 1.81	M36 x 2	B	SKK12-25S-PK-GS-C6F	SKK12-25S-VK-GS-C6F
		30	30 1.18	50 1.97	M42 x 2	B	SKK12-30S-PK-GS-C6F	SKK12-30S-VK-GS-C6F
	315 4568	38	34 1.34	60 2.36	M52 x 2	B	SKK12-38S-PK-GS-C6F	SKK12-38S-VK-GS-C6F

- For DKO connection
- According to ISO 8434-1 / DIN 2353
- Version A: one-piece design
- Version B: screwed design

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".


* Standard option for North America is FPM (Viton®).

Protection Cap

Standard material: Steel
For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SKK12-06L-VK-KK-C6F)

For further information on materials, sealings or protection caps, please see page B22.

Bulkhead SSKK12



Threads

*1 Special thread: buttress thread S12,65 x 1,5

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**

For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".

For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".

For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is **FPM (Viton®)**.

Thread	Dimensions (mm/in)		Order Codes	
	G	Hex	NBR	FPM* (Standard Option-North America)
S12*1	63	19	SSKK12-P-C6F	SSKK12-V-C6F
	2.48	0.75		


Protection Cap

Standard material: Steel

For ordering the plastic protection cap version please add "-KK" to the order code. (e.g. SSKK12-V-KK-C6F)

For further information on materials, sealings or protection caps, please see page B22.

Swivel Run Tee with JIC Connection SGV-JIC Type F/M



Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**


For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".

For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".


For further information please consult STAUFF.

Thread	Dimensions (^{mm} / _{in})								Order Codes
inch	Ø d1	Ø d2	l1	l2	l3	l4	Hex A	Hex B	
7/16–20 UNF	7,49	4,9	9	14	37	8	27	17	SGV-7/16UNF-04-JIC1/4-F/M-C6F
	.29	.19	.35	.55	1.46	.31	1.06	.67	
9/16–18 UNF	11,05	8,1	10,5	14	37,5	8,5	27	19	SGV-7/16UNF-06-JIC3/8-F/M-C6F
	.44	.32	.41	.55	1.48	.33	1.06	.75	
3/4–16 UNF	15,9	10,8	10,5	16,7	43,7	12	30	22	SGV-7/16UNF-08-JIC1/2-F/M-C6F
	.63	.43	.41	.66	1.72	.47	1.18	.87	
1-1/16–12 UNF	21,6	16,9	15,4	21,9	50,4	13,5	36	32	SGV-7/16UNF-12-JIC3/4-F/M-C6F
	.85	.66	.61	.86	1.98	.53	1.42	1.26	
1-5/16–12 UNF	27,9	23,2	17,3	23,1	53,1	15	41	41	SGV-7/16UNF-16-JIC1-F/M-C6F
	1.10	.91	.68	.91	2.09	.59	1.61	1.61	

Adaptor SAD12



Version A



Version B



Thread	Dimensions (mm/in)	Version	Order Codes NBR	FPM* (Standard Option-North America)
G	h			
M16 x 2	33 1.30	A	SAD12/20-P-C6F	SAD12/20-V-C6F
M16 x 1,5	33 1.30	A	SAD12/15-P-C6F	SAD12/15-V-C6F
Plug in	31 1.22	B	SAD12/10-P-C6F	SAD12/10-V-C6F

Threads

*1 Special thread: buttress thread S12,65 x1,5


Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".


Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).



Gauge Adaptor SMA15



Direct Gauge Adaptor SMD15

Gauge Adaptor SMA12

Direct Gauge Adaptor SMD12



Thread	Dimensions (mm/in)	Hex A	Order Codes NBR	FPM* (Standard Option-North America)
G	h			
G1/4	51 2.01	19 .75	SMA12-G1/4-P-OR-C6F	SMA12-G1/4-V-OR-C6F
G1/2	61 2.40	27 1.06	SMA12-G1/2-P-OR-C6F	SMA12-G1/2-V-OR-C6F
1/4 NPT	51 2.01	19 .75	SMA12-1/4NPT-P-C6F	SMA12-1/4NPT-V-C6F
1/2 NPT	61 2.40	27 1.06	SMA12-1/2NPT-P-C6F	SMA12-1/2NPT-V-C6F
G1/4	35 1.38	19 .75	SMD12-G1/4-P-OR-C6F	SMD12-G1/4-V-OR-C6F
G1/2	45 1.77	27 1.06	SMD12-G1/2-P-OR-C6F	SMD12-G1/2-V-OR-C6F
1/4 NPT	35 1.38	19 .75	SMD12-1/4NPT-P-C6F	SMD12-1/4NPT-V-C6F
1/2 NPT	45 1.77	27 1.06	SMD12-1/2NPT-P-C6F	SMD12-1/2NPT-V-C6F

Threads

*1 Special thread: buttress thread S12,65 x1,5

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".


Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Snubber on request.

Test Coupling with Ball Check



Fast coupling for

- Monitoring and control of pressure
- Venting
- Sampling in high- and low-pressure systems

Advantages

- Test system at working pressure
- Leak proof connection before **ball check** is open
- Simple connection to measurement, control and switching devices

Working Pressure

- Max. working pressure 400 bar / 5801 PSI
For SMK Type G and K the recommended working pressure of fitting manufacturer should be noted.

Materials

- Metal Parts:**
Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
- Ball:** Stainless Steel

Sealings:

P = NBR (Buna-N®)

(Temperature range -20 °C ... +100 °C / -4 °F ... +212 °F)

Note: Internal sealings made of FPM, even for standard NBR-type.

V = FPM (Viton®)*

(Temperature range -20 °C ... +200 °C / -4 °F ... +392 °F)

*** Standard option for North America is FPM (Viton®)**

E = EPDM Ethylene Propylene Diene Monomer Rubber

(for Brake fluid,

Temperature range -40 °C ... +150 °C / -40 °F ... +302 °F)

For ordering NBR or EPDM sealings please replace "V" with "P" or "E".

Media

- Suitable for hydraulic oils and other Mineral oil based fluids
(Check compatibility of seal material)
- For use with other liquid media please consult STAUFF

SMK10
Test Coupling
with Port Connection




SMK10 Type G
Test Coupling complete
with Straight Fitting



SMK10 Type K
Test Coupling for
24° Cone Fittings



Test Coupling with Port Connection SMK10



Thread G	Sealing	Working Pressure (^{bar} /PSI)	Dimensions (^{mm} / ⁱⁿ)			Order Codes	
			h1	h2	Hex	NBR	FPM* (Standard Option-North America)
M8 x 1	Type A	250	17,5	8,5	12	SMK10-M8x1-PA-C6F	SMK10-M8x1-VA-C6F
		3625	.69	.33	.47		
M10 x 1	Type A	400	17,5	9,8	12	SMK10-M10x1-PA-C6F	SMK10-M10x1-VA-C6F
		5801	.69	.39	.47		
R1/8 K	Type D	400	17,5	8	12	SMK10-R1/8K-PD-C6F	SMK10-R1/8K-VD-C6F
		5801	.69	.31	.47		

Metal Parts


Standard material: Steel, zinc/nickel-plated = C6F (CrVI-free)

Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

For further information on materials or seals, please see page B28.
Further thread versions possible with use of thread adaptors SRS20, please see page B32.



Gauge Adaptor SMA10



Thread G	Dimensions (^{mm} / ⁱⁿ)		Order Codes	
	h	Hex A	NBR	FPM* (Standard Option-North America)
G1/4	57	19	SMA10-G1/4-P-OR-C6F	SMA10-G1/4-V-OR-C6F
	2.24	.75		
G1/2	67	27	SMA10-G1/2-P-OR-C6F	SMA10-G1/2-V-OR-C6F
	2.64	1.06		
1/4 NPT	57	19	SMA10-1/4NPT-P-C6F	SMA10-1/4NPT-V-C6F
	2.24	.75		
1/2 NPT	67	27	SMA10-1/2NPT-P-C6F	SMA10-1/2NPT-V-C6F
	2.64	1.06		

Metal Parts

Standard material: Steel, zinc/nickel-plated = C6F (CrVI-free)


Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Snubber on request.

Test Coupling complete with Straight Fitting SMK10 Type G



- Compression ring fittings acc. to ISO 8434-1 / DIN 2353

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**

Sealings

For ordering NBR sealings replace "V" with "P".


For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).


For further information on materials or sealings, please see page B28.

Series	PN (bar/psi)	Pipe Ød	Dimensions (mm/in)						Order Codes	
			~l1	l2	h	Hex A	Hex B		NBR	FPM* (Standard Option-North America)
L	315 4568	6	51 2.01	21 .83	29,5 1.16	24 .94	14 .55		SMK10-06L-PG-C6F	SMK10-06L-VG-C6F
		8	51 2.01	21 .83	29,5 1.16	24 .94	17 .67		SMK10-08L-PG-C6F	SMK10-08L-VG-C6F
		10	53 2.09	23 .91	29,5 1.16	24 .94	19 .75		SMK10-10L-PG-C6F	SMK10-10L-VG-C6F
		12	53 2.09	23 .91	31 1.22	27 1.06	22 .87		SMK10-12L-PG-C6F	SMK10-12L-VG-C6F
		15	55 2.17	25 .98	32,5 1.28	30 1.18	27 1.06		SMK10-15L-PG-C6F	SMK10-15L-VG-C6F
		18	57 2.24	24 .94	33,5 1.32	32 1.26	32 1.26		SMK10-18L-PG-C6F	SMK10-18L-VG-C6F
	160 2320	22	61 2.40	28 1.10	33,5 1.32	36 1.42	36 1.42		SMK10-22L-PG-C6F	SMK10-22L-VG-C6F
		28	61 2.40	28 1.10	38 1.50	41 1.61	41 1.61		SMK10-28L-PG-C6F	SMK10-28L-VG-C6F
		35	69 2.72	26 1.02	40,5 1.59	46 1.81	50 1.97		SMK10-35L-PG-C6F	SMK10-35L-VG-C6F
		42	71 2.80	25 .98	45 1.77	55 2.17	60 2.36		SMK10-42L-PG-C6F	SMK10-42L-VG-C6F
S	400 5801	6	55 2.17	25 .98	29,5 1.16	24 .94	17 .67		SMK10-06S-PG-C6F	SMK10-06S-VG-C6F
		8	55 2.17	25 .98	29,5 1.16	24 .94	19 .75		SMK10-08S-PG-C6F	SMK10-08S-VG-C6F
		10	57 2.24	24 .94	29,5 1.16	24 .94	22 .87		SMK10-10S-PG-C6F	SMK10-10S-VG-C6F
		12	57 2.24	24 .94	29,5 1.16	24 .94	24 .94		SMK10-12S-PG-C6F	SMK10-12S-VG-C6F
		14	63 2.50	27 1.06	31 1.22	27 1.06	27 1.06		SMK10-14S-PG-C6F	SMK10-14S-VG-C6F
		16	63 2.50	26 1.02	32,5 1.28	30 1.18	30 1.18		SMK10-16S-PG-C6F	SMK10-16S-VG-C6F
		20	69 2.72	26 1.02	35,5 1.40	36 1.42	36 1.42		SMK10-20S-PG-C6F	SMK10-20S-VG-C6F
		25	75 2.95	27 1.06	38 1.50	41 1.61	46 1.81		SMK10-25S-PG-C6F	SMK10-25S-VG-C6F
		30	81 3.19	28 1.10	40,5 1.59	46 1.81	50 1.97		SMK10-30S-PG-C6F	SMK10-30S-VG-C6F
		38	91 3.58	29 1.14	45 1.77	55 2.17	60 2.36		SMK10-38S-PG-C6F	SMK10-38S-VG-C6F

Test Coupling for 24° Cone Fittings SMK10 Type K



Version A



Version B



Series	PN (bar/psi)	Pipe Ød	Dimensions (mm/in)			Thread	Version	Order Codes	
			I3	Hex A	G			NBR	FPM* (Standard Option-North America)
L	315 4568	6	15,5 .61	14 .55		M12 x 1,5	A	SMK10-06L-PK-GS-C6F	SMK10-06L-VK-GS-C6F
		8	15,5 .61	17 .67		M14 x 1,5	A	SMK10-08L-PK-GS-C6F	SMK10-08L-VK-GS-C6F
		10	16,5 .65	19 .75		M16 x 1,5	A	SMK10-10L-PK-GS-C6F	SMK10-10L-VK-GS-C6F
		12	17,5 .69	22 .87		M18 x 1,5	A	SMK10-12L-PK-GS-C6F	SMK10-12L-VK-GS-C6F
		15	21 .83	27 1.06		M22 x 1,5	B	SMK10-15L-PK-GS-C6F	SMK10-15L-VK-GS-C6F
		18	19,5 .77	32 1.26		M26 x 1,5	B	SMK10-18L-PK-GS-C6F	SMK10-18L-VK-GS-C6F
	160 2320	22	20,5 .81	36 1.42		M30 x 2	B	SMK10-22L-PK-GS-C6F	SMK10-22L-VK-GS-C6F
		28	25 .98	41 1.61		M36 x 2	B	SMK10-28L-PK-GS-C6F	SMK10-28L-VK-GS-C6F
		35	30 1.18	50 1.97		M45 x 2	B	SMK10-35L-PK-GS-C6F	SMK10-35L-VK-GS-C6F
		42	31 1.22	60 2.36		M52 x 2	B	SMK10-42L-PK-GS-C6F	SMK10-42L-VK-GS-C6F
S	400 5801	6	14,5 .57	17 .67		M14 x 1,5	A	SMK10-06S-PK-GS-C6F	SMK10-06S-VK-GS-C6F
		8	16,5 .65	19 .75		M16 x 1,5	A	SMK10-08S-PK-GS-C6F	SMK10-08S-VK-GS-C6F
		10	16,5 .65	22 .87		M18 x 1,5	A	SMK10-10S-PK-GS-C6F	SMK10-10S-VK-GS-C6F
		12	17,5 .69	24 .94		M20 x 1,5	A	SMK10-12S-PK-GS-C6F	SMK10-12S-VK-GS-C6F
		14	19,5 .77	27 1.06		M22 x 1,5	B	SMK10-14S-PK-GS-C6F	SMK10-14S-VK-GS-C6F
		16	18 .71	30 1.18		M24 x 1,5	B	SMK10-16S-PK-GS-C6F	SMK10-16S-VK-GS-C6F
		20	24 .94	36 1.42		M30 x 2	B	SMK10-20S-PK-GS-C6F	SMK10-20S-VK-GS-C6F
		25	26 1.02	46 1.81		M36 x 2	B	SMK10-25S-PK-GS-C6F	SMK10-25S-VK-GS-C6F
	315 4568	30	30 1.18	50 1.97		M42 x 2	B	SMK10-30S-PK-GS-C6F	SMK10-30S-VK-GS-C6F
		38	34 1.34	60 2.36		M52 x 2	B	SMK10-38S-PK-GS-C6F	SMK10-38S-VK-GS-C6F

- For DKO connection
- According to ISO 8434-1 / DIN 2353

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**


Sealings

For ordering NBR sealings replace "V" with "P".
For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

For further information on materials or sealings, please see page B28.

Thread Adaptor SRS20



Metal Parts

Standard Material SRS20:

Steel, zinc/nickel-plated = **C6F (CrVI-free)**

For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".

For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".

For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Sealing Details



Metal Joint Type B



Elastomeric Sealing Type C




Taper Type D
(suitable sealant required)



O-ring Type E

Thread	Sealing	Dimensions (mm/in)			Order Codes
G		h1	h2	Hex	
M10 x 1	Type B	15,5 .61	8,5 .33	17 .67	SRS20-M10x1-B-C6F
M12 x 1,5		15 .59	12 .47	19 .75	SRS20-M12x1,5-B-C6F
M14 x 1,5		15 .59	12 .47	19 .75	SRS20-M14x1,5-B-C6F
M16 x 1,5		8 .31	12 .47	22 .87	SRS20-M16x1,5-B-C6F
M18 x 1,5		15 .59	12 .47	24 .94	SRS20-M18x1,5-B-C6F
M22 x 1,5		10,5 .41	14 .55	27 1.06	SRS20-M22x1,5-B-C6F
G1/8		15,5 .61	8 .31	17 .67	SRS20-G1/8-B-C6F
G1/4		15 .59	12 .47	19 .75	SRS20-G1/4-B-C6F
G3/8		10,5 .41	12 .47	22 .87	SRS20-G3/8-B-C6F
G1/2		10,5 .41	14 .55	27 1.06	SRS20-G1/2-B-C6F
M12 x 1,5	Type C	15 .59	12 .47	19 .75	SRS20-M12x1,5-PC-C6F
M14 x 1,5		15 .59	12 .47	19 .75	SRS20-M14x1,5-PC-C6F
M18 x 1,5		15 .59	12 .47	24 .94	SRS20-M18x1,5-PC-C6F
G1/8		16 .63	8 .31	17 .67	SRS20-G1/8-PC-C6F
G1/4		15 .59	12 .47	19 .75	SRS20-G1/4-PC-C6F
G3/8		10,5 .41	12 .47	22 .87	SRS20-G3/8-PC-C6F
G1/2		10,5 .41	14 .55	27 1.06	SRS20-G1/2-PC-C6F
R1/4 K		13 .51	12 .47	17 .67	SRS20-R1/4K-D-C6F
R3/8 K	Type D	13 .51	14 .55	19 .75	SRS20-R3/8K-D-C6F
R1/2 K		8 .31	19 .75	22 .87	SRS20-R1/2K-D-C6F
1/4 NPT		10 .39	15 .59	17 .67	SRS20-1/4NPT-D-C6F
1/2 NPT		8 .31	20 .79	22 .87	SRS20-1/2NPT-D-C6F
7/16-20 UNF		9 .35	9,1 .36	17 .67	SRS20-7/16UNF-PE-C6F
1/2-20 UNF	Type E	15 .59	9,2 .36	17 .67	SRS20-1/2UNF-PE-C6F
9/16-18 UNF		15,5 .61	10 .39	19 .75	SRS20-9/16UNF-PE-C6F
7/8-14 UNF		11 .43	16 .63	27 1.06	SRS20-7/8UNF-PE-C6F
M14 x 1,5		14,5 .57	11 .43	19 .75	SRS20-M14x1,5-PE-C6F
M16 x 1,5		8,5 .33	12,5 .49	22 .87	SRS20-M16x1,5-PE-C6F
M22 x 1,5		10 .39	15 .59	27 1.06	SRS20-M22x1,5-PE-C6F
M27 x 2		10 .39	18,5 .73	32 1.26	SRS20-M27x2-PE-C6F

Thread Adaptor SRS15



Thread	Sealing	Dimensions (mm/in)			Order Codes
G		h1	h2	Hex	
M14 x 1,5	Type B	24 .95	12 .47	19 .75	SRS15-M14x1,5-B-C6F
M16 x 1,5		24 .95	12 .47	22 .87	SRS15-M16x1,5-B-C6F
M18 x 1,5		24 .95	12 .47	24 .95	SRS15-M18x1,5-B-C6F
M20 x 1,5		10,5 .41	14 .55	27 1.06	SRS15-M20x1,5-B-C6F
G3/8		24 .95	12 .47	22 .87	SRS15-G3/8-B-C6F
G1/2		10,5 .41	14 .55	27 1.06	SRS15-G1/2-B-C6F
M14 x 1,5	Type C	24 .95	12 .47	19 .75	SRS15-M14x1,5-PC-C6F
M16 x 1,5		24 .95	12 .47	22 .87	SRS15-M16x1,5-PC-C6F
M18 x 1,5		24 .95	12 .47	24 .95	SRS15-M18x1,5-PC-C6F
G3/8		24 .95	12 .47	22 .87	SRS15-G3/8-PC-C6F

Metal Parts

Standard material SRS15:

Steel, zinc/nickel-plated = **C6F (CrVI-free)**

For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".

For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".

For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).


Sealing Details



Metal Joint Type B



Elastomeric Sealing Type C



Welding Adaptor SAS



Thread	Port Connection	Dimensions (mm/in)		Order Codes
G		h	Ød	
M10 x 1	Type A	25 .98	20 .79	SAS-M10x1
G1/8	Type B/C	25 .98	20 .79	SAS-G1/8
G1/4		30 1.18	22 .87	SAS-G1/4
G3/8		30 1.18	25 .98	SAS-G3/8
1/4 NPT	Type D	25 .98	20 .79	SAS-1/4NPT
1/2-20 UNF	Type E	25 .98	20 .79	SAS-1/2UNF

Metal Parts

Standard material: **S235 (St 37), phosphated**

Pressure Gauge SPG



Area of Application

- Mechanical pressure measurement

Characteristics

- Suitable for hydraulic oil and gaseous media that do not corrode any copper base alloy
- Available in nominal sizes 63 and 100
- Thread form: BSP (G1/4 and G1/2), NPT (1/4NPT and 1/2NPT), -4 SAE
- Housing made of Stainless Steel (1.4301)
- Sight glass made of Acrylic
- Glycerine filled
- Standard dual scales with pressure indication in bar and PSI
- U-bolt or flange mounting kit on request

Consult STAUFF before you use SPG with other media.

Further information and order codes on pressure gauges please see pages D6 - D7, Diagnostics section.

Technical Data

Protection rating: IP 65 (EN 60 529 / IEC 529)
 Accuracy class SPG-063: 2/1/2 % of span
 (per ASME B 40.100 Grade A)
 Accuracy class SPG-100: 1% of span
 (per ASME B 40.100 Grade 1A)
 Environmental temp. range: - 20 °C ... + 60 °C / - 4 °F ... + 140 °F
 Temperature range medium: max. + 60 °C / max. + 140 °F
 Subject to technical modifications


Options (on request)

- Protective rubber cap
- Additional scale readings including personalisation
- U-bolt and flange mounting kits are available separately as spare parts
- Additional pressure ranges up to 1000 bar / 14503 PSI max.

Further information and order codes on gauge isolator valves please see the Valves section.

Standard Pressure Range Options	
(^{bar} /PSI)	(^{bar} /PSI)
-1,02 bar ... 0 bar	68,95
-30 inHg ... 0 PSI	1000
-1,02 bar ... 2.07 PSI	103,42
-30 inHg ... 30 PSI	1500
2,07	137,90
30	2000
4,14	206,84
60	3000
6,89	275,79
100	4000
11,03	344,74
160	5000
13,79	413,69
200	6000
20,68	517,11
300	7500
34,74	689,48
500	10000
41,37	
600	Others on request

Adjustable Gauge Fitting EMV



Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**
 For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
 For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering NBR sealings replace "V" with "P".
 For ordering EPDM sealings replace "V" with "E".

* Standard option for North America is FPM (Viton®).

Dimensions (^{mm} / _m)				Order Codes	
G1	G2	h	Hex	NBR	FPM* (Standard Option-North America)
G1/4	G1/4	42 1.65	19 .75	EMV-G1/4-P-OR-PC-C6F	EMV-G1/4-V-OR-VC-C6F
G1/4	G1/2	47 1.85	19 .75	EMV-G1/4G1/2-P-OR-PC-C6F	EMV-G1/4G1/2-V-OR-VC-C6F
G1/2	G1/4	51 2.01	27 1.06	EMV-G1/2G1/4-P-OR-PC-C6F	EMV-G1/2G1/4-V-OR-VC-C6F
G1/2	G1/2	55,5 2.19	27 1.06	EMV-G1/2-P-OR-PC-C6F	EMV-G1/2-V-OR-VC-C6F

Pressure Test Kit SMB

Single Gauge Kit SMB20-A1	
Component Parts	Order Codes
1 Hose assembly (60 in)	SMS20-1524mm-B
1 Direct gauge adaptor 1/4 NPT	SMD20-1/4NPT-C6F
1 Union	SSV20-C6F
1 Pressure gauge 7500 PSI	WPG-063-07500-5-S-N04
2 Test coupling 1/8 NPT	SMK20-1/8NPT-VD-C6F
3 Test coupling 1/4 NPT	SMK20-1/4NPT-VD-C6F
2 Test coupling 7/16 UNF	SMK20-7/16UNF-VE-C6F
2 Test coupling 9/16 UNF	SMK20-9/16UNF-VE-C6F
1 Female QD fitting 1/4 NPT	SQD-04NF-C



Double Gauge Kit SMB20-B1	
Component Parts	Order Codes
1 Hose assembly (60 in)	SMS20-1524mm-B
2 Direct gauge adaptor 1/4 NPT	SMD20-1/4NPT-C6F
1 Union	SSV20-C6F
1 Pressure gauge 7500 PSI	WPG-063-07500-5-S-N04
1 Pressure gauge 1000 PSI	WPG-063-01000-5-S-N04
2 Test coupling 1/8 NPT	SMK20-1/8NPT-VD-C6F
2 Test coupling 1/4 NPT	SMK20-1/4NPT-VD-C6F
1 Test coupling 7/16 UNF	SMK20-7/16UNF-VE-C6F
1 Test coupling 9/16 UNF	SMK20-9/16UNF-VE-C6F
1 Female QD fitting 1/4 NPT	SQD-04NF-C



Triple Gauge Kit SMB20-C1	
Component Parts	Order Codes
2 Hose assembly (60 in)	SMS20-1524mm-B
3 Direct gauge adaptor 1/4 NPT	SMD20-1/4NPT-C6F
2 Union	SSV20-C6F
1 Pressure gauge -30 inHg ... 30 PSI	WPG-063-03030-5-S-N04
1 Pressure gauge 7500 PSI	WPG-063-07500-5-S-N04
1 Pressure gauge 1000 PSI	WPG-063-01000-5-S-N04
2 Test coupling 1/8 NPT	SMK20-1/8NPT-VD-C6F
2 Test coupling 1/4 NPT	SMK20-1/4NPT-VD-C6F
1 Test coupling 7/16 UNF	SMK20-7/16UNF-VE-C6F
1 Test coupling 9/16 UNF	SMK20-9/16UNF-VE-C6F
1 Female QD fitting 1/4 NPT	SQD-04NF-C



Custom kits available upon request.

For further information please see page D10, Diagtronics section.

Please consult STAUFF.

Multi Gauge Kit SMB20-E1-X (see table below for X)	
Component Parts	Order Codes
3 Test coupling 1/4 NPT	SMK20-1/4NPT-VD-C6F
3 Test coupling 7/16 UNF	SMK20-7/16UNF-VE-C6F
3 Test coupling 9/16 UNF	SMK20-9/16UNF-VE-C6F
3 Gauge adaptor	SMA20-1/4NPT-V-C6F
3 Union adaptor	SSV20/20-C6F
2 Test hose (12 in)	SMS20-305mm-B
2 Test hose (24 in)	SMS20-610mm-B
2 Test hose (60 in)	SMS20-1524mm-B
1 Swivel run tee -4 JIC	SGV-7/16UNF-04-JIC1/4-F/M
1 Swivel run tee -6 JIC	SGV-7/16UNF-06-JIC3/8-F/M
1 Swivel run tee -8 JIC	SGV-7/16UNF-08-JIC1/2-F/M
1 Female QD fitting 1/4 NPT	SQD-04NF-C



Multi Gauge Kit SMB

SMB20-E1-5	SMB20-E1-6	SMB20-E1-7	SMB20-E1-8
SPG-063-03030-5-S-N04	SPG-063-03030-5-S-N04	SPG-063-03030-5-S-N04	SPG-063-03030-5-S-N04
SPG-063-00600-5-S-N04	SPG-063-00600-5-S-N04	SPG-063-00600-5-S-N04	SPG-063-00600-5-S-N04
SPG-063-03000-5-S-N04	SPG-063-01500-5-S-N04	SPG-063-01500-5-S-N04	SPG-063-01000-5-S-N04
SPG-063-05000-5-S-N04	SPG-063-03000-5-S-N04	SPG-063-03000-5-S-N04	SPG-063-01500-5-S-N04
SPG-063-10000-5-S-N04	SPG-063-05000-5-S-N04	SPG-063-05000-5-S-N04	SPG-063-03000-5-S-N04
	SPG-063-10000-5-S-N04	SPG-063-07500-5-S-N04	SPG-063-05000-5-S-N04
		SPG-063-10000-5-S-N04	SPG-063-07500-5-S-N04
			SPG-063-10000-5-S-N04

Each pressure gauge includes a protective gauge cover SPG-063-RBB and a direct gauge adapter SMD-1/4NPT-C6F

Gauges included in Standard Kit

5 Gauge Kit: see table SMB20-E1-5
6 Gauge Kit: see table SMB20-E1-6
7 Gauge Kit: see table SMB20-E1-7
8 Gauge Kit: see table SMB20-E1-8

Technical Data for Test Hose



		A	B (Standard Version)	C	D	
Nominal Bore (DN)		(mm)	DN 2	DN 4		
Max. Working Pressure (PN)		(bar / PSI)	400 / 5801	630 / 9135	340 / 4931	630 / 9135
Min. Burst Pressure		(bar / PSI)	1100 / 15954	1900 / 27557	850 / 12328	1900 / 27557
Testing Pressure		(bar / PSI)	600 / 8702	950 / 13778	570 / 8267	950 / 13779
Pressure Rating in bar / PSI at Indicated Temperature	at 0 °C / 32 °F	(bar / PSI)	488 / 7077	768 / 11138	463 / 6715	768 / 11139
	at 30 °C / 86 °F		440 / 6381	693 / 10051	418 / 6063	693 / 10051
	at 50 °C / 122 °F		400 / 5801	630 / 9137	380 / 5511	630 / 9137
	at 80 °C / 176 °F		344 / 4989	542 / 7861	327 / 4743	542 / 7861
	at 100 °C / 212 °F		308 / 4467	485 / 7034	293 / 4250	485 / 7034
Working Temperature		(°C / °F)	-35 °C ... +100 °C / -31 °F ... +212 °F (momentary +120 °C / +248 °F)			
Inside Diameter		(mm / in)	2 / .08		4 / .16	
Outside Diameter		(mm / in)	5 / .20		8,6 / .34	
Bending Radius	at working pressure	(mm / in)	20 / .79		40 / 1.57	
	at -20 °C / 4 °F		30 / 1.18		60 / 2.36	
Max. Coil Length		(m / ft)	100 / 328			
Weight / m		(g / oz)	16 / .50		42 / 1.35	
Inner / Outer Tube			PA			
Reinforcement			Synthetic Fibre			
Standard hose end material is Steel 11 S Mn Pb 30 (1.0718), zinc/ nickel-plated (Type 15: Steel, <u>black</u> zinc/nickel-plated)						
Stainless Steel: V2A (1.4305/AISI 303), V4A (1.4571/AISI 316Ti) on request						

Standard Hose






STAUFF-Test 20/20

STAUFF-Test 15/15

STAUFF-Test 12/12*2

STAUFF-Test 10/10

Gauge Adaptor



- Max. Working Pressure: 400 bar / 5801 PSI
- Burst Pressure: 1100 bar / 15954 PSI
- Pressure/t° factor:
 - to 0 °C 122 %
 - at 30 °C 110 %
 - at 50 °C 100 %
 - at 80 °C 86 %
 - at 100 °C 77 %


- Max. Working Pressure: 630 bar / 9137 PSI
- Burst Pressure: 1900 bar / 27557 PSI
- Pressure/t° factor:
 - to 0 °C 122 %
 - at 30 °C 110 %
 - at 50 °C 100 %
 - at 80 °C 86 %
 - at 100 °C 77 %

- Max. Working Pressure: 400 bar / 5801 PSI
- Burst Pressure: 1100 bar / 15954 PSI
- Pressure/t° factor:
 - to 0 °C 122 %
 - at 30 °C 110 %
 - at 50 °C 100 %
 - at 80 °C 86 %
 - at 100 °C 77 %

- Max. Working Pressure: 400 bar / 5801 PSI
- Burst Pressure: 1100 bar / 15954 PSI
- Pressure/t° factor:
 - to 0 °C 122 %
 - at 30 °C 110 %
 - at 50 °C 100 %
 - at 80 °C 86 %
 - at 100 °C 77 %


- Gauge adaptor 1/4 NPT, G1/2 and 1/2 NPT on request
- Gauge adaptor available for all STAUFF-Test series

Order Code STAUFF Test Hose



SMS *1		20		/ M		1219		B		C6F			
Hose End 1 (see pages B38 - B43)				Hose End 2 (see pages B38 - B43)				Length		DN / Hose Size		Material Hose End	
20	A	J	only specify when 2 different hose ends are required				Length in mm (see L above)		A = DN 2 400 bar / 5802 PSI		Standard hose end material is Steel		
15	S	D							B*2 = DN 2 630 bar / 9137 PSI		11 S Mn Pb 30 (1.0718), zinc/nickel-plated = C6F		
12	K	B							C*3 = DN 4 340 bar / 4931 PSI		Type 15: Steel, <u>black</u> zinc/nickel-plated = C6F		
10	L	U					Standard Lengths see table below.		D*3 = DN 4 630 bar / 9137 PSI		Stainless Steel:		
M	G	P									V2A (1.4305/AISI 303),		
N	F	etc.									V4A (1.4571/AISI 316Ti) on request		
W	C												
*1 for gaseous media type SGS - Test hoses are perforated													
*2 Standard test hose option for North America is version B.													
*3 Type C and D - are perforated													






Standard Length L*	
in mm	in in
305	12
610	24
915	36
1219	48
1524	60
1829	72
2438	96
3048	120
6096	240








Order Code STAUFF Hose End






HE	20	B	C6F
Hose End (see pages B38 - B43)			DN / Hose Size
20	A	J	A = DN 2 400 bar / 5802 PSI
15	S	D	B = DN 2 630 bar / 9137 PSI
12	K	B	C = DN 4 340 bar / 4931 PSI
10	L	U	D = DN 4 630 bar / 9137 PSI
M	G	P	
N	F	etc.	
W	C		
			Material Hose End
			Standard hose end material is Steel
			11 S Mn Pb 30 (1.0718), zinc/nickel-plated = C6F
			Type 15: Steel, black zinc/nickel-plated = C6F
			Stainless Steel:
			V2A (1.4305/AISI 303),
			V4A (1.4571/AISI 316Ti) on request






STAUFF Hose End

Hose End	Description	Type	G	Hex (mm/in)	DN Hose Size
	STAUFF-Test Screw-type suitable for test points		20	M16 x 2	2 and 4
			15	M16 x 1,5	
			12	S12,62 x 1,5	
	STAUFF-Test Screw-type 90° elbow suitable for test points	0	20	M16 x 2	2
			15	M16 x 1,5	
			12	S12,62 x 1,5	
	STAUFF-Test Screw-type 90° elbow suitable for test points (short wire version)	0X	20	M16 x 2	17 .67 2
			15	M16 x 1,5	
			12	S12,62 x 1,5	
	STAUFF-Test Plug in-type		10	Plug in system	2
	Gauge adaptor BSP-thread for G3/8, G1/2, M14 x 1,5 and M20 x 1,5 swivel nut like type N	M	1/4	G1/4	2 and 4
			1/2	G1/2	
			3/8	G3/8	2
			14	M14 x 1,5	
			20	M20 x 1,5	






Hose End	Description	Type	G	Hex (mm/in)	DN Hose Size
	90° elbow gauge adaptor BSP-thread for G1/2 swivel nut like type N	W	1/4	G1/4	19 .75
			1/2	G1/2	27 1.06
	Gauge adaptor NPT-thread for 1/4 NPT swivel nut like type M	N	1/4	1/4 NPT	19 .75
			1/2	1/2 NPT	27 1.06
	90° elbow gauge adaptor NPT-thread for 1/2 NPT swivel nut like type N	A	1/4	1/4 NPT	19 .75
			1/2	1/2 NPT	27 1.06
	Standpipe for compression ring fittings according to ISO 8434-1 / DIN 2353 Note: Standpipe version is not in accordance with the state of the art. Use at own risk. We recommend the use of the series K, R or L.	S	4	4 LL	2
			6	6 L - 6 S	2 and 4
			8	8 L - 8 S	
			10	10 L - 10 S	2
			12	12 L - 12 S	
			1/4	1/4	2 and 4
	Standpipe for compression ring fittings according to ISO 8434-1 / DIN 2353 90° elbow Note: Standpipe version is not in accordance with the state of the art. Use at own risk. We recommend the use of the series K, R or L.	SG	6	6 L - 6 S	2 and 4
			8	8 L - 8 S	

STAUFF Hose End





Hose End	Description	Type	G	Hex (mm/in)	DN Hose Size
	Seal with O-ring for 24° cone fitting according to ISO 8434-1 / DIN 2353 c/w swivel nut	K	6 L	M12 x 1,5	14 .55
			8 L	M14 x 1,5	17 .67
			10 L	M16 x 1,5	19 .75
			12 L	M18 x 1,5	22 .87
			6 S	M14 x 1,5	17 .67
			8 S	M16 x 1,5	19 .75
			10 S	M18 x 1,5	22 .87
			12 S	M20 x 1,5	24 .94
	Seal with O-ring for 24° cone fitting according to ISO 8434-1 / DIN 2353 c/w swivel nut 45° elbow	R	6 L	M12 x 1,5	14 .55
			6 S	M14 x 1,5	14 .67
	Seal with O-ring for 24° cone fitting according to ISO 8434-1 / DIN 2353 c/w swivel nut 90° elbow	L	6 L	M12 x 1,5	14 .55
			8 L	M14 x 1,5	17 .67
			10 L	M16 x 1,5	19 .75
			6 S	M14 x 1,5	17 .67
			8 S	M16 x 1,5	19 .75
			10 S	M18 x 1,5	24 .94
	Male thread according to DIN 3852-B	G	12	M12 x 1,5	17 .67
			1/8	G1/8	14 .55
			1/4	G1/4	19 .75
			1/2	G1/2	27 1.06
	Male thread NPT according to ANSI-standard	F	1/8	1/8 NPT	13 .51
			1/4	1/4 NPT	17 .67

Hose End	Description	Type	G	Hex (mm/in)	DN Hose Size
	Male thread for 24° cone fitting according to ISO 8434-1 / DIN 2353	C	6 L	M12 x 1,5	14 .55
			8 L	M14 x 1,5	17 .67
			6 S	M14 x 1,5	17 .67
			8 S	M16 x 1,5	17 .67
	Male thread according to SAE J 514	J	1/4	7/16-20 UNF	14 .55
			5/16	1/2-20 UNF	14 .55
			3/8	9/16-18 UNF	17 .67
	Universal sealing head with swivel nut for 24° cone fitting according to ISO 8434-1 / DIN 2353	D	6 L	M12 x 1,5	14 .55
			8 L	M14 x 1,5	17 .67
			10 L	M16 x 1,5	19 .75
			12 L	M18 x 1,5	22 .87
			6 S	M14 x 1,5	17 .67
			8 S	M16 x 1,5	19 .75
			10 S	M18 x 1,5	22 .87
			12 S	M20 x 1,5	24 .94
	Universal sealing head with swivel nut for 24° cone fitting according to ISO 8434-1 / DIN 2353 90° elbow	Q	10 L	M16 x 1,5	19 .75
			10 S	M18 x 1,5	22 .87
	Sealing head with swivel nut for cone fitting according to DIN EN 560	B	1/8	G1/8	12 .47
			1/4	G1/4	17 .67


STAUFF Hose End

Hose End	Description	Type	G	Hex (mm/in)	DN Hose Size
	Sealing head with swivel nut according to SAE J 514 37° cone	U	1/4	7/16–20 UNF	14 .55
			5/16	1/2–20 UNF	17 .67
			3/8	9/16–18 UNF	19 .75
	Sealing head with swivel nut according to SAE J 516 45° cone	UR	1/4	7/16–20 UNF	14 .55 2
	Sealing head with swivel nut according to SAE J 516 37° cone 90° elbow	E	1/4	7/16–20 UNF	14 .55 2 and 4
	Sealing head with swivel nut according to SAE J 516 45° cone 90° elbow	ER	1/4	7/16–20 UNF	14 .55 2
	Test hose for air brake systems	P	2	M16 x 1,5	19 .75 2

STAUFF Hose End

Hose End	Description	Type	G	Hex (mm/in)	DN Hose Size
	Sealing head with swivel nut 60° cone	H	1/4	G1/4	17 .67 2 and 4
	Screw-type ORFS according to SAE J 1453	T	9/16	9/16-18 UNF	17 .67 2
			11/16	11/16-16 UN	21 .83
	Screw-type ORFS according to SAE J 1453 90° elbow	V	11/16	11/16-16 UN	21 .83 2 and 4
	Hose end with integrated check valve	RV	20	M16 x 2	2
			15	M16 x 1,5	

Hose Connector SSV



Sealings

Internal sealings made of FPM (Viton®).

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**

Standard material SSV15:


Steel, black zinc/nickel-plated = **C6F (CrVI-free)**

For ordering **V2A (1.4305 / AISI 303)** replace "C6F" with "V2A".

For ordering **V4A (1.4571 / AISI 316Ti)** replace "C6F" with "V4A".

Thread	Dimensions (^{mm} / _{in})			Order Codes
G	I1	I2	Hex	
M16 x 2	42,5 1.67	18,5 .73	17 .67	SSV20-C6F
M16 x 1,5	42,5 1.67	18,5 .73	17 .67	SSV15-C6F
S12,65 x 1,5	31 1.22	12,5 .49	14 .55	SSV12-C6F


Sampling Hose Adaptor SHA



Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**

Dimensions (^{mm} / _{in})						Order Code
Ød1	Ød2	I1	I2	I3	G	
22	5,5	13	23	24	18	SHA20-5.5MM-C6F
.87	.22	.51	.91	.94	.71	




Pressure Test Connection for Compressed-Air Pneumatic Braking Equipment (according to ISO 3583)




Test Coupling with Female Connection Port



Gauge Adaptor with Test Coupling



Banjo Fitting with Test Coupling





Triple Manifold Block with Test Couplings


Custom-designed test coupling solutions in addition to the Original-STAUFF-Test range according to customers's specifications or based on STAUFF developments.

If you have similar requirements please consult STAUFF.


Port Connections and Sealing Details


Type A	Type A - Threaded port according to factory standard Sealing: O-ring Type A				
	Thread	Dimensions (mm/in)			
	G	d1 +0,1	t1 min.	t2 min	
	M8 x 1	9,5 .37	11 .43	15,5 .61	
	M10 x 1	11,5 .45	12 .47	16,5 .64	

Type B and C	Type B and C - Threaded port type X acc. to DIN 3852 Part 1 and 2; ISO 9974-1 (metric); ISO 1179-1 (inch) Sealing: Metal joint Type B / Elastomeric sealing Type C				
	Thread	Dimensions (mm/in)			
	G	d1 min.	t1 min.	t2 min.	a max.
	M10 x 1	15 .59	8 .31	10 .39	1 .04
	M12 x 1,5	18 .71	12 .47	15 .59	1,5 .06
	M14 x 1,5	20 .79	12 .47	15 .59	1,5 .06
	M16 x 1,5	23 .91	12 .47	15 .59	1,5 .06
	M18 x 1,5	25 .98	12 .47	15 .59	2 .08
	M20 x 1,5	27 1.06	14 .55	17 .67	2 .08
	M22 x 1,5	28 1.10	14 .55	17 .67	2,5 .10
	G1/8	15 .59	8,5 .33	10,5 .41	1 .04
	G1/4	20 .79	12,5 .49	15,5 .61	1,5 .06
	G3/8	23 .91	12,5 .49	15,5 .61	2 .08
	G1/2	28 1.10	14,5 .57	18,5 .73	2,5 .10

Type D	Type D - Parallel threaded port type Z according to DIN 3852 Part 2 (inch) Sealing: Taper Type D suitable sealant required		
	Thread	Dimensions (mm/in)	
	G	t1 min.	t2 min.
	Rp1/8	5,5 .22	9,5 .37
	Rp1/4	8,5 .33	13,5 .53
	Rp3/8	8,5 .33	13,5 .53
	Rp1/2	10,5 .41	16,5 .65

Port Connections and Sealing Details

Type D	Type D - Taper threaded port according to ANSI/ASME B1.20.1-1983 (NPT) Sealing: Taper Type D suitable sealant required		
	Thread	Dimensions (^{mm} / _{in})	
	G	t1 min.	t2 min.
	1/8-27 NPT	6,9 .27	11,6 .46
	1/4-18 NPT	10 .39	16,4 .65
	1/2-14 NPT	13,6 .54	22,6 .89

	Type E - Threaded port according to ISO 6149-1 (metric); ISO 11926-1 (UNF) Sealing: O-ring Type E							
	Thread	Dimensions (^{mm} / _{in})						
	G	d1 +0,1	d2 min.	t1 min.	t2 min.	a +0,4	b max.	z° ±1°
	M10 x 1	11,1 .44	16 .63	10 .39	11,5 .45	1,6 .06	1 .04	12°
	M12 x 1,5	13,8 .54	19 .75	11,5 .45	14 .55	2,4 .09	1,5 .06	15°
	M14 x 1,5	15,8 .62	21 .83	11,5 .45	14 .55	2,4 .09	1,5 .06	15°
	M16 x 1,5	17,8 .70	24 .94	13 .51	15,5 .61	2,4 .09	1,5 .06	15°
	M22 x 1,5	23,8 .94	29 1.14	15,5 .61	18 .71	2,4 .09	2 .08	15°
	M27 x 2	29,4 1.16	34 1.34	19 .75	22 .87	3,1 .91	2 .08	15°
	5/16–24 UNF	9,1 .36	17 .67	10 .39	12 .47	1,9 .07	1,6 .06	12°
	7/16–24 UNF	12,4 .49	21 .83	11,5 .45	14 .55	2,4 .09	1,6 .06	12°
	1/2–20 UNF	14 .55	23 .91	11,5 .45	14 .55	2,4 .09	1,6 .06	12°
	9/16–18 UNF	15,65 .62	25 .98	12,7 .50	15,5 .61	2,5 .10	1,6 .06	12°
	7/8–14 UNF	23,95 .94	34 1.34	16,7 .66	20 .79	2,5 .10	2,4 .09	15°